




REV - DESCRIPT - DATE - APPRVD
A - UPDATED NOTES - 2006/06/16 - YK.
B - CHG SOLDER TAIL - 2006/07/19 - YK.
C - UPDATED MATERIALS - 2006/08/18 - YK.
D - STAKING ADDED: NOT APPROVED BY CUSTOMER - MAY 23,07
E - O RING SIZE CHANGED - SEPT28,07 - A.G.
F - TIGHTENING TORQUE ADDED - OCT23,07 - A.G.











NOTES:

1. MATERIAL:
   - SHELL: ZINC ALLOY 50 MICRO INCH MINIMUM NICKEL PLATING.
   - CONTACTS: COPPER ALLOY 30 MICRO INCH GOLD OVER 50 MICRO INCH NICKEL PLATING.
   - INSULATOR: THERMOPLASTIC POLYESTER RESIN (DSM) 94V-0 FLAMMABILITY RATING.
   - GASKETS: SILICONE RUBBER S7001R, 70 DUROMETER.
   - SEALING COMPOUND: STYCAST 2651 WITH CATALYST 11

2. FEATURES: SEALED CONNECTOR IN THE MATED AND UNMATED CONDITIONS.

3. OPERATING TEMPERATURE: -40°C TO +105°C.

4. ENVIRONMENT PERFORMANCE: IP67.

5. PART IS RoHS COMPLIANT.

6. REAR SEAL TO WITHSTAND TEMPERATURE EXPOSURE OF SOLDER BATH 265°C FOR 8 SEC & SOLDER PREHEAT 150°C FOR 180 SEC.

7. SEALED TO WITHSTAND PRESSURE UP TO 5 PSI AFTER HIGH TEMPERATURE EXPOSURE.

8. RECOMMENDED TORQUE FOR SCREW TIGHTENING:
   - STEEL SCREW WITH MORE THAN .090" THREAD ENGAGEMENT: 4.0 TO 5.75 INCH-LBS
   - BRASS SCREW: 3.1 TO 4.5 INCH-LBS.

AMPHENOL PART NUMBER: MDB-E09SE-860

DO NOT SCALE DRAWING

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT PERMISSION FROM AMPHENOL CANADA CORP.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETER
TOLERANCES ARE:
DECIMALS .XX ± .10 .X ± .25
ANGLES ± 1°

MATERIAL AND FINISH

REF.

CODE IDENT. NO.

APPROVALS	DATE
DRAWN Y.KUZYK	2006/07/24
DESIGNED S.SEMENOV	2006/07/24
CHECKED	
QA APP'D	
IE APP'D	
DWG APP'D -	2006/07/24


Amphenol Canada Corp.

TITLE: MDB 9 SOCKETS CONNECTOR


SIZE	DWG. NO.	REV.
C	P-MDB-E09SE-860	F

SCALE	PROJECT	SHEET
3:1	MDB	1 OF 2

REV - DESCRIPT - DATE - APPRVD
SEE PAGE 1



PCB LAYOUT



RECOMMENDED PANEL CUTOUT

Amphenol Canada RoHS Compliant EU 2002/95/EC

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETER TOLERANCES ARE: DECIMALS .XX ± .10 .X ± .25 ANGLES ± 1°	APPROVALS	DATE	Amphenol Canada Corp.
	DRAWN Y.KUZYK	2006/07/24	
	DESIGNED S.SEMENOV	2006/07/24	TITLE: MDB 9 SOCKETS CONNECTOR
MATERIAL AND FINISH	CHECKED		
	QA APP'D		
REF.	IE APP'D		SIZE C | DWG. NO. P-MDB-E09SE-860 | REV. F
CODE IDENT. NO.	DWG APP'D -	2006/07/24	SCALE 4:1 | PROJECT MDB | SHEET 2 OF 2

DO NOT SCALE DRAWING
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT PERMISSION FROM AMPHENOL CANADA CORP.