INDUSTRIAL@AMPHENOL TRUSTED GLOBALLY

432RS9W

Wall mounted socket

2CMA167191R1000



Surface socket-outlet, earthing sleeve position 9h, rated current 32A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Blue

GENERAL

Product Name	Wall mounted socket
Product ID	2CMA167191R1000
Function	Surface socket outlet
EAN	73926966719
Catalog Description	Surface socket-outlet, 9h, 32A, IP67, 3P+N+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2416566
E-Number Norway	2416566
E-Number Sweden	2416566
Standards	IEC 60309-1, -2
RoHS Status	Following EU Directive 2011/65/EU

TECHNICAL

Product Main Type	TRS
Color	Blue
Number of Poles	5
Clock Position	9Hour
Rated Current	32 ampere
Rated Voltage	120/208 ... 144/250 volt
Frequency	50 hertz|60 hertz
Degree of Protection	IP67|IP69
Cable Cross-Section	2.5...10 mm²
Housing Material	Thermoplastic (PBT)
Plug Angle	
Product Group	Tough&Safe

DIMENSIONS

Product Net Width	99 millimetre
Product Net Height	178 millimetre
Product Net Length	178 millimetre
Product Net Depth	178 millimetre
Product Net Weight	0.48 kilogram

PACKAGING

Package Width	135 millimetre
Package Height	200 millimetre
Package Gross Weight	0.55 kilogram
Package Length	140 millimetre
Package Units	box 1 piece