316RAM9

# Panel mounted socket

# 2CMA170014R1000



Panel mounted socket, earthing sleeve position 9h, rated current 16A, IP44 splashproof, minimized flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Blue

## GENERAL

| | |
|---|---|
| **Product Name** | Panel mounted socket |
| **Product ID** | 2CMA170014R1000 |
| **Function** | Panel mounted socket |
| **EAN** | 73926960146 |
| **Catalog Description** | Socket-outlet, panel mounting, 9h, 16A, IP44, minimized flange, angled, 3P+E |
| **Country of Origin** | Czech Republic (CZ) |
| **E-Number Finland** | 2416470 |
| **E-Number Norway** | 2416470 |
| **E-Number Sweden** | 2416470 |
| **Standards** | IEC 60309-1, -2 |
| **RoHS Status** | Following EU Directive 2011/65/EU |

## TECHNICAL

| | |
|---|---|
| **Product Main Type** | ERAM |
| **Color** | Blue |
| **Number of Poles** | 4 |
| **Clock Position** | 9Hour |
| **Rated Current** | 16 ampere |
| **Rated Voltage** | 200 … 250 volt |
| **Frequency** | 50 hertz\|60 hertz |
| **Degree of Protection** | IP44 |
| **Cable Cross-Section** | 1.5…4 mm² |
| **Housing Material** | Plastic (PA) |
| **Plug Angle** | Angled |
| **Product Group** | Easy&Safe |

## DIMENSIONS

| | |
|---|---|
| **Product Net Width** | 83 millimetre |
| **Product Net Height** | 89 millimetre |
| **Product Net Length** | 99 millimetre |
| **Product Net Depth** | 99 millimetre |
| **Product Net Weight** | 0.24 kilogram |

## PACKAGING

| | |
|---|---|
| **Package Width** | 154 millimetre |
| **Package Height** | 378 millimetre |
| **Package Gross Weight** | 2.4 kilogram |
| **Package Length** | 182 millimetre |
| **Package Units** | box 10 piece |