164J2B11 × OBSOLETE

ALCOSWITCH

TE Internal #: 1-1437569-3

TE Internal Description: 164J2B11=REC 2-POS KY PLL BOTH

View on TE.com >

Switches > Keylock Switches



Configuration (Pole-Throw): **Double Pole - Double Throw**

Remove Key: **Both Positions**

Soldering Type: **Hand**

Operating Function: **1 NO & 1 NC**

Contact Current Rating: **5 A**

Features

Product Type Features

Actuator Style	Key Actuator
Switch Type	Key Lock Switch

Configuration Features

Number of Positions	2
Number of Actuators	Single
Configuration (Pole-Throw)	Double Pole - Double Throw
Operating Function	1 NO & 1 NC
Panel Cutout Size	16 (Diameter) mm[.625 (Diameter) in]

Electrical Characteristics

Insulation Resistance	100 MΩ
Dielectric Withstanding Voltage (Max)	1500 VAC
Contact Current Rating	5 A
Contact Resistance	20 mΩ
Operating Voltage	20 VDC

Contact Features

Contact Finish	Gold

Mechanical Attachment

Product Mount Type	Panel Mount

Housing Features

Remove Key	Both Positions

Usage Conditions

Oil-Tight	No
Operating Temperature (Max)	50 °C[122 °F]

Operation/Application

Durability Rating	100000 Cycles

Other

Soldering Type	Hand

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought




TE Part #1-480350-2
01P CMNL CAP HSG F/H RED



TE Part #643326-4
13P MTA156 HDR ASSY W/O#4



TE Part #2232044-2
2P, RAST 5 Tab Header, THV



TE Part #2331410-1
DET SW4.2X3.6X1.2 GW VERT.(UP) NO AG RL



TE Part #1-6609107-6
PSL0XSS60=C1043



TE Part #30926
TERMINAL,DG R 16-14 6



TE Part #5-104439-3
5X4 MTE RCPT SR PLAIN .100CL



TE Part #5-104439-7
2X8 MTE RCPT SR PLAIN .100CL



TE Part #DTS20F13-35AA
RECP ASSY



TE Part #5-104439-6
2X7 MTE RCPT SR PLAIN .100CL

Documents

Product Drawings

164J2B11=REC 2-POS KY PLL BOTH

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-1437569-3_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1437569-3_B.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1-1437569-3_B.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

SWITCHES_CORE_PROGRAM_CATALOG

English