1-2370702-1 ✔ ACTIVE


DEUTSCH | DEUTSCH DT

TE Internal #: 1-2370702-1

12 V / 24 V / 48 V, 2 Position, Automotive Housing for Female Terminals, Wire-to-Wire, 5.46 mm [.215 in] Centerline, Sealable, Gray, DEUTSCH DT

View on TE.com >

Automotive Parts > Automotive Connectors > Automotive Housings > DEUTSCH DT Connectors with snap cap




Nominal Voltage Architecture: **12 V, 24 V, 48 V**

Connector & Housing Type: **Housing for Female Terminals**

Number of Positions: **2**

Sealable: **Yes**

Operating Temperature Range: **-55 – 125 °C [-67 – 257 °F]**

All DEUTSCH DT Connectors with snap cap (36)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	Integrated in Housing
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Blank Cavity Position	0
Connector Seal Code	E Seal
Number of Positions	2
Number of Rows	1

Electrical Characteristics

Operating Voltage	250 VDC
Nominal Voltage Architecture	12 V, 24 V, 48 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Gray

Contact Features

Contact Size	Size 16
Contact Type	Socket
Mating Pin Diameter	1.55 mm[.061 in]
Contact Current Rating (Max)	13 A

Mechanical Attachment

Strain Relief	Add By Accessory
Terminal Position Assurance	No
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PA GF
Centerline (Pitch)	5.46 mm[.215 in]

Dimensions

Compatible Insulation Diameter Range	1.35 – 3.05 mm[.053 – .12 in]
Product Width	16.6 mm[.654 in]
Product Length	36.2 mm[1.425 in]
Connector Height	17.1 mm[.673 in]

Usage Conditions

Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operating Temperature (Max)	125 °C[257 °F]

Operation/Application

Circuit Application	Power

Industry Standards

IP Rating	IP68, IP6K9K

Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	12mm Flame Test per Standard UL-94

Packaging Features

Packaging Quantity	1200
Packaging Method	Box

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # W2S-P012
WEDGE LOCK, 2P, PLG, GRN, SL RET, DT



TE Part # 0413-217-1605
SEALING PLUG, SIZE 16, LOCKING, WHT

Also in the Series | DEUTSCH DT



Automotive Connector Locks & Position Assurance(91)




Automotive Housings(767)




Connector Caps & Covers(1)




Connector Strain Relief(35)



Infotainment & Multimedia Cable Assemblies(1)



Other Automotive Connector Accessories(27)




Rectangular Backshells & Clamps(3)


Customers Also Bought



TE Part #1060-16-0677
PIN, SF, SIZE 16, 16-20, SN/SN



TE Part #776262-1
14POS,PIN DIA 1.3,HDR ASSY, 180DEG,COD 1



TE Part #925715-2
MATENLOK PIN .140



TE Part #926980-2
CI 2 STIFT



TE Part #1534841-1
COVER FOR 12POS,MQS



TE Part #2338212-1
PLUG SOCKET ASSY, 4P, W2W, SEALED COAX



TE Part #2373965-1
CPA,AMPSEAL



TE Part #368376-1
81P REC HSG ASSY() BLK



TE Part #827039-1
CIC.SOCKET ASSY.



TE Part #925264-1
7P CIC MIX BU GEH

Documents

Product Drawings

2POS,DIA 1.5MM,SOC HSG ASSY,SLD,COD NEUT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2370702-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2370702-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2370702-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

DEUTSCH DTM SEALED FLANGE RECEPTACLE

English

Product Specifications

Application Specification

English