1-5229913-1 ✔ ACTIVE

CHAMP | CHAMP Docking Connectors

TE Internal #: 1-5229913-1

50 Position D-Shaped Connector, Receptacle, Cable-to-Board / Cable-to-Cable, Cable Mount (Free-Hanging), CHAMP Docking Connectors

View on TE.com >

Connectors > D-Shaped Connectors > IDC D-Sub: Receptacle Kit, Signal, 50, 2.16 mm







Number of Positions: **50**

Connector & Housing Type: **Receptacle**

Connector System: **Cable-to-Board, Cable-to-Cable**

Connector Mounting Type: **Cable Mount (Free-Hanging)**

Centerline (Pitch): **2.16 mm [.085 in]**

All IDC D-Sub: Receptacle Kit, Signal, 50, 2.16 mm (8)

Features

Product Type Features

Connector & Housing Type	Receptacle
Connector System	Cable-to-Board, Cable-to-Cable
Connector Product Type	Connector Kit
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	50
Number of Rows	2
Compatible With Wire & Cable Type	Discrete Wire, Round Jacketed Cable

Body Features

Connector Profile	Standard
Cover Material	Polyethylene, Polyphenylene Oxide

Contact Features

Contact Underplating Material	Palladium Nickel
Contact Mating Area Plating Material	Gold or Gold Flash
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material Thickness	.76 µm[30 µin]
Contact Current Rating (Max)	.5 A, 1 A
Contact Options	Supplied – Uninstalled

Termination Features

Termination Method to Wire & Cable	Insulation Displacement (IDC)

Mechanical Attachment

Mating Retention	With
Mating Retention Type	Screwlocks
Thread Size	4-40
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	Polyphenylene Oxide
Centerline (Pitch)	2.16 mm[.085 in]

Dimensions

Accepts Cable Insulation Diameter Range	8.89 – 10.8 mm[.35 – .425 in]
Solid Wire Size	26 – 24 AWG
Accepts Cable Diameter (Max)	10.8 mm[.425 in]
Compatible Insulation Diameter (Max)	1.14 mm[.045 in]
Stranded Wire Size	.33 mm^2
Wire Size	24 AWG

Usage Conditions

Operating Temperature Range	-40 – 75 °C[-40 – 167 °F]

Operation/Application

Shielded	Yes
Circuit Application	Signal

Packaging Features

Packaging Method	Bag
Packaging Quantity	1

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Triphenyl phosphate (TPP) (1.5% in 20567588257) **Article Safe Usage Statements:** Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-357-D658
IDC D-Sub: Plug Assembly, Signal, Cable to Cable, 2.16 mm




TE Part # CAT-357-D601
IDC D-Sub: Receptacle Assembly, Signal, 2.16 mm

Also in the Series | CHAMP Docking Connectors



Connector Caps & Covers(27)




Connector Hardware(26)




Connector Strain Relief(2)



Docking Connectors(19)



IDC D-Sub Connectors(41)



Panel Mount D-Sub Connectors(5)

Customers Also Bought



TE Part #66107-4
III+ PIN,26-24,30AU/FL,LP



TE Part #6-66461-3
SKT,.062 DIA,.025 SQ POST,LP



TE Part #350429-1
03P UMNL PIN HDR ASSY NATL



TE Part #552032-1
ASSY, PLUG, 50 POS, B SLOT



TE Part #1-745491-7
09 HDE MS RCPT,22-26,LEAD FREE



TE Part #1-745492-8
09 HDE MS PLUG,22-26,LEAD FREE



TE Part #1393249-9
W58-XB1A4A-15=W58



TE Part #1-1734099-0
Champ 050 series,plug assembly



TE Part #1-1734101-0
Champ050 series,100pos,Au over PdNi



TE Part #1-6609028-9
20VK6=F7357 S0

Documents

CAD Files

Customer View Model

ENG_CVM_CVM_1-5229913-1_O.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-5229913-1_O.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-5229913-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.