160212 ✔ ACTIVE




PLASTI-GRIP

TE Internal #: 160212

Spade Flange Tongue Terminal, 16 – 14 AWG, #8 / M4 Stud, 4.34 mm [.171 in] Stud Diameter, Closed Barrel, Flanged, Tin Plating, PLASTI-GRIP

View on TE.com >

Terminals & Splices > Spade Terminals



Spade Terminal Type: **Spade Flange Tongue Terminal**

Wire Size: **2050 – 5180 CMA**

Stud Size: **#8, M4**

Features

Product Type Features

Stud Size	#8, M4
Sealable	No
Wire Insulation Support Retention Type	Insulation Support

Electrical Characteristics

Voltage Rating	600 V

Body Features

Product Weight	.185 g
Insulation Sleeve Color	Blue
Stripe Color	Blue

Contact Features

Spade Terminal Type	Spade Flange Tongue Terminal
Barrel Type	Closed
Terminal Orientation	Flanged
Terminal Plating Material	Tin

Mechanical Attachment

Wire Insulation Support	Without

Dimensions

Wire Size	2050 – 5180 CMA
Stud Diameter	4.34 mm[.171 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	19.02 mm[.749 in]
Compatible Insulation Diameter (Max)	1.95 mm[.195 in]
Compatible Insulation Diameter Range	1.95 mm[.195 in]

Usage Conditions

Insulation Option	Partially Insulated
Operating Temperature Range	0 – 90 °C[0 – 194 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

Industry Standards

Government Qualified Terminal	No

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | PLASTI-GRIP




Compression Connectors(3)



Crimp Wire Pins, Tabs & Ferrules(20)



Ring Terminals(310)



Spade Terminals(158)



Splices(45)

Customers Also Bought



TE Part #34155
PG SPD 22-16 COMM 22-18 MIL 8



TE Part #34163
TERMINAL,PG R 16-14 5/16



TE Part #34853
TERMINAL,PG R 12-10 8



TE Part #58583-1
PROCRIMP HT&D SUPRSEAL 1.5 SER



TE Part #130014
TERM, R, PG, 22-16, M5



TE Part #160136
TERM, RING, PLASTI-GRIP, 16-14, M10



TE Part #160296
RING TNG PLASTI-G



TE Part #165035
PLASTI-GRIP, RING, 12-10 1/4



TE Part #170360-3
MINI UNIVERSAL M-N-L PIN



TE Part #350561-7
UMNL PIN 24-18 .0126 AU/NI/BR

Documents

Product Drawings

P.G. SPADE FLG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160212_K1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160212_K1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160212_K1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English