170030-1 ✔ ACTIVE

FASTIN-FASTON | FASTIN-FASTON 250



TE Internal #: 170030-1

Quick Disconnect Tab, Uninsulated, 20 – 14 AWG, .51 – 2.08 mm² Wire, 6.35 mm [.25 in] Tab Width, F-Crimp, Straight, Brass, FASTIN-FASTON 250

View on TE.com >

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.51 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Locking Lance Height	1.2 mm
Wire Insulation Support	With
Mating Retention Type	Locking Lance
Extraction Force	4.9 Newton

Dimensions

Product Length	26.5 mm[1.04 in]
Compatible Insulation Diameter Range	2.16 – 3.43 mm[.085 – .135 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	.51 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	4000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as

EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2150041-2
OCEAN_2.0_Applicator-E-110F180F-REA



TE Part # 7-2150041-7
OCEAN_2.0_SPARE_PART_KIT-110F180F



TE Part # 720725-1
DAHT 250 FASTIN-ON TAB REC 18-14 ASSY




TE Part # 2819183-1
.250 SERIES FASTIN FASTON REC.



TE Part # 7-2150041-8
OCEAN_2.0_OV_CRIMPER_OPTION-110F180OV

Also in the Series | FASTIN-FASTON 250



Crimp Terminal Housings(192)



Insertion & Extraction Tools(2)



Quick Disconnects(217)

Customers Also Bought



TE Part #170030-2
FF 250 TAB 20-14AWG TPBR



TE Part #170031-1
FF 250 REC 20-14AWG BR




TE Part #1318386-2
025 16P PLUG HSG ASSY H-TYP




TE Part #7-1452653-2
MCON 1.2 LL REC SRC AU



TE Part #1827120-1
SQUIB LOCKING BUTTON



TE Part #1903608-4
0.50 SERIES CONN 12POS PLUG HOUSING ASSY



TE Part #1903614-1
0.5 6POS LOCK HOUSING



TE Part #1981562-1
1.0 SERIES CAVITY PLUG



TE Part #1445994-1
120A HSG SUBASY,GRAY



TE Part #175046-1
FF 187 TAB 0.5-1.25MM2 PTBR

Documents

Product Drawings

FF 250 TAB 20-14AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_170030-1_S.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_170030-1_S.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_170030-1_S.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Crimping of 250 Series Tab and Receptacle Contacts

Japanese

Application Specification

Japanese

Application Specification

Japanese

Crimping of 250 Series Tab and Receptacle Contacts

Japanese

Instruction Sheets

Instruction Sheet (non U.S.)

Japanese

Instruction Sheet (non U.S.)

Japanese