1969729-4 ✔ ACTIVE

Economy Power 2.5

TE Internal #: 1969729-4


PCB Mount Header, Vertical, Wire-to-Board, 4 Position, 2.5 mm [.098 in] Centerline, Fully Shrouded, Tin (Sn), Through Hole - Solder, Economy Power 2.5

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles







PCB Connector Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Wire-to-Board**

Number of Positions: **4**

Centerline (Pitch): **2.5 mm [.098 in]**

Features

Product Type Features

Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Columns	4
Number of Loaded Positions	4
PCB Mount Orientation	Vertical
Number of Positions	4
Number of Rows	1
Number of Power Positions	4

Electrical Characteristics

Operating Voltage	250 VAC

Body Features

Primary Product Color	Natural

Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 µm[50 µin]
Contact Layout	Inline
Contact Base Material	Brass
Contact Mating Area Plating Material	Tin (Sn)
Contact Mating Area Plating Material Thickness	2.032 µm[80 µin]
Contact Type	Pin
Contact Current Rating (Max)	4.2 A
PCB Contact Termination Area Plating Material	Tin

Termination Features

Termination Post & Tail Length	3.4 mm[.134 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Retention Type	Locking Tab
Mating Alignment Type	Polarization
PCB Mount Retention Type	Kinked Legs
PCB Mount Alignment	Without
Mating Retention	With
PCB Mount Retention	With
Connector Mounting Type	Board Mount
Mating Alignment	With

Housing Features

Centerline (Pitch)	2.5 mm[.098 in]
Housing Material	Thermoplastic

Dimensions

Connector Width	6.4 mm[.25 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]

Connector Height	8.8 mm[.346 in]
Connector Length	12.5 mm[.492 in]

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Shielded	No
Circuit Application	Power

Industry Standards

Compatible With Agency/Standards Products	UL
UL Rating	Recognized
Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	600
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUL 2017 (174) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles'(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts




TE Part # 1969729-7
EP2.5 Shrouded HDR ASSY 7P VERT w /o boss



TE Part # 1969729-3
EP2.5 Shrouded HDR ASSY 3P VERT w /o boss



TE Part # 1-1969730-6
EP2.5 SHROUDED HDR ASSY 16P VERTICAL



TE Part # 1969729-9
EP2.5 Shrouded HDR ASSY 9P VERT w /o boss



TE Part # 2132415-4
EP2.5 Shrouded HDR ASSY 4P VERT w /o boss



TE Part # 1-1969729-0
EP2.5 Shrouded HDR ASSY 10P VERT w/oboss



TE Part # 1-1969730-3
EP2.5 SHROUDED HDR ASSY 13P VERTICAL



TE Part # 1969729-2
EP2.5 Shrouded HDR ASSY 2P VERT w /o boss



TE Part # 1969729-5
EP2.5 Shrouded HDR ASSY 5P VERT w /o boss




TE Part # 1-1969730-5
EP2.5 SHROUDED HDR ASSY 15P VERTICAL


Also in the Series | Economy Power 2.5




Connector Contacts(6)



Connector Hardware(49)




PCB Headers & Receptacles(533)



Rectangular Connector Housings(305)




Rectangular Power Connectors(835)



Standard Rectangular Connectors(305)



Wire-to-Board Connector Assemblies & Housings(134)



Wire-to-Board Headers & Receptacles (533)

Customers Also Bought



TE Part #1969729-5
EP2.5 Shrouded HDR ASSY 5P VERT w /o boss



TE Part #2292457-3
3P, RAST 5 HEADER, PL, SHROUDED



TE Part #5-2299683-3
EP2.5 HDR 3P VERT W/O BOSS, TAPING,GREEN



TE Part #1721766-5
PCH-112D2-WG

TE Part #1744530-6
EP 2.5 Header no Boss 06P, Red

TE Part #2-1744530-4
EP2.5 HDR ASSY 4P VERT W/O BOSS, BLUE

TE Part #2-1744530-5
EP2.5 HDR ASSY 5P VERT W/O BOSS, BLUE

TE Part #2-1744530-6
EP2.5 HDR ASSY 6P VERT W/O BOSS, BLUE

TE Part #4-1744530-5
EP2.5 HDR ASSY 5P VERT W/O BOSS, BLACK

TE Part #6-1744530-4
EP2.5 HDR ASSY 4P VERT W/O BOSS, YELLOW

Documents

Product Drawings

EP2.5 Shrouded HDR ASSY 4P VERT w/o boss

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1969729-4_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1969729-4_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1969729-4_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Agency Approvals

VDE Certificate

English