2085123-1 ✔ ACTIVE

TE Internal #: 2085123-1

PCB Mount Plug, Right Angle, Board-to-Board, 76 Position, 2.5 mm / 7.5 mm [.098 in / .295 in] Centerline, Gold (Au), Through Hole - Solder

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Plug**

Connector System: **Board-to-Board**

Number of Positions: **76**

Number of Rows: **3**

Centerline (Pitch): **2.5 mm, 7.5 mm [.098 in, .295 in]**

Features

Product Type Features

Mixed & Hybrid Header	Yes
Connector Shape	Rectangular
PCB Connector Type	PCB Mount Plug
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Positions	76
Number of Rows	3
PCB Mount Orientation	Right Angle
Number of Power Positions	4
Number of Signal Positions	72

Electrical Characteristics

Operating Voltage	250 VDC

Body Features

Primary Product Color	Black

Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 µm[50 µin]
Mating Square Post Dimension	.64 mm[.025 in]
Mating Tab Width	7 mm[.275 in]
PCB Contact Termination Area Plating Material Thickness	3.05 µm[120 µin]
Contact Layout	Matrix
Contact Base Material	Brass Alloy, Copper Alloy, Phosphor Bronze
Mating Tab Thickness	1.25 mm[.049 in]
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Blade, Pin
Contact Current Rating (Max)	3 A, 35 A
Contact Mating Area Plating Material Thickness	.76 µm[30 µin]

Termination Features

Termination Post & Tail Length	3.05 mm[.12 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

PCB Mount Retention Type	Flange w/Mounting Holes
Connector Mounting Type	Board Mount
Mating Alignment	Without
PCB Mount Alignment	Without
PCB Mount Retention	With

Housing Features

Centerline (Pitch)	2.5 mm, 7.5 mm[.098 in][.295 in]
Housing Material	Thermoplastic Glass Reinforced

Dimensions

Connector Width	14 mm[.551 in]
Connector Height	14 mm[.551 in]
Connector Length	149.5 mm[5.88 in]

Row-to-Row Spacing	2.5 mm[.098 in]
PCB Thickness (Recommended)	1.57 – 3.18 mm[.062 – .125 in]

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]

Operation/Application

Circuit Application	Power & Signal

Industry Standards

Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	64
Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1926720-2
AssyMINIPAKHDL2p15s2p RAplugBdlk

Customers Also Bought



TE Part #194010-1
PIN ASSY..070




TE Part #194017-1
PIN ASSY..070



TE Part #1648384-1
708-73-01109=SA CONTACT,SKT



TE Part #1676441-2
RN 0805 80K6 0.1% 10PPM 1KRL



TE Part #2-1761606-7
IDC LOW PRO HDR 20P VERT LA




TE Part #1-1825910-0
FSM6JH=6MM TACT SWITCH, HIGH TEMP



TE Part #2085119-1
24PIN RECTANGULAR POWER CONNECTORS

TE Part #3-2172067-2
M8 MALE R/A PNL.4P.PCB (AU)



TE Part #3-2213767-5
AV19 SPL 3A MOVE RING LED GREEN 24V



TE Part #1-2834011-2
2POS 3.5MM TOP ENTRY SCREWLESS CONN.

Documents

Product Drawings

CONN SOCKET ASSY STRAIGHT SOLDER FLATPAQ

English

CAD Files

Customer View Model

ENG_CVM_CVM_2085123-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2085123-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2085123-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.