2350203-1 ✔ ACTIVE

SFP28



TE Internal #: 2350203-1

zSFP+, Cage Assembly, Signal, Operating Temperature Range -55 – 105 °C [-67 – 221 °F], Data Rate (Max) 32 Gb/s, 3 Ports

View on TE.com >

Connectors > Pluggable IO Connectors & Cages




Pluggable I/O Product Type: **Cage Assembly**

Sealable: **No**

Circuit Application: **Signal**

Operating Temperature Range: **-55 – 105 °C [-67 – 221 °F]**

Data Rate (Max): **32 Gb/s**

Features

Product Type Features

Cage Type	Ganged
Pluggable I/O Product Type	Cage Assembly
Sealable	No
Form Factor	zSFP+

Configuration Features

Number of Ports	3
Port Matrix Configuration	1 x 3

Electrical Characteristics

Data Rate (Max)	32 Gb/s

Contact Features

Contact Current Rating (Max)	.5 A
Contact Underplating Material	Nickel
Contact Mating Area Plating Material	Gold (Au)
PCB Contact Termination Area Plating Material	Gold Flash

Termination Features

Termination Method to PCB	Through Hole - Solder
Termination Post & Tail Length	2.5 mm[.098 in]

Housing Features

Cage Material	Stainless Steel

Dimensions

PCB Thickness (Recommended)	2.25 mm[.089 in]

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Heat Sink Compatible	No
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Method	Tray

Other

Included Lightpipe	No
EMI Containment Feature Type	Internal/External EMI Springs

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1761394-1
DUST COVER, SFP, GANGED & STACKED

Customers Also Bought



TE Part #CAT-SF59-C117ST123
SFP+ Stacked Cage Assemblies




TE Part #2110304-1
SFP+ 1x1 Cage Assembly, Solder Tail



TE Part #2173239-1
1x3 Cage Assy Bhnd Bzl QSFP28



TE Part #4-2176325-2
CRGP 0402 27K 1%



TE Part #2288221-1
CFP2 EMI/DUST PLUG



TE Part #2350202-1
ZSFP+ 1X3 CAGE ASSEMBLY, EON

Documents

CAD Files
3D PDF
3D

Customer View Model

ENG_CVM_CVM_2350203-1_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2350203-1_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2350203-1_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English