281739-5 ✔ ACTIVE



AMPMODU | AMPMODU HE 13/HE 14



TE Internal #: 281739-5

PCB Mount Header, Vertical, Wire-to-Board, 10 Position, 2.54 mm [.1 in] Centerline, Partially Shrouded, Tin (Sn), AMPMODU HE 13/HE 14

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles > HE13/HE14 TH Headers, DRST

PCB Connector Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Wire-to-Board**

Number of Positions: **10**

Centerline (Pitch): **2.54 mm [.1 in]**

All HE13/HE14 TH Headers, DRST (13)

Features

Product Type Features

Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	10
Number of Rows	2

Electrical Characteristics

Insulation Resistance	1000 MΩ
Dielectric Withstanding Voltage (Max)	500 V

Body Features

Primary Product Color	Blue

Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.4 µm[55.11 µin]
Mating Square Post Dimension	.64 mm[.025 in]
PCB Contact Termination Area Plating Material Thickness	3.25 µm[127.95 µin]
Contact Shape & Form	Square
Contact Layout	Matrix
Contact Mating Area Length	7 mm[.275 in]
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Tin (Sn)
Contact Mating Area Plating Material Finish	Matte
Contact Mating Area Plating Material Thickness	.8 µm[31 µin]
Contact Type	Pin
Contact Current Rating (Max)	3 A

Termination Features

Termination Post & Tail Length	2.9 mm[.114 in]
Square Termination Post & Tail Dimension	.63 mm[.025 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Panel Mount Feature	Without
Mating Alignment Type	Polarization
PCB Mount Alignment	Without
Mating Retention	With
PCB Mount Retention	Without
Connector Mounting Type	Board Mount
Mating Alignment	With

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	High Temperature Thermoplastic

Dimensions

Row-to-Row Spacing	2.54 mm[.1 in]
Connector Width	7.62 mm[.3 in]
Connector Height	11.4 mm[.449 in]
Connector Length	12.7 mm[.5 in]

Usage Conditions

Operating Temperature Range	-40 – 100 °C[-40 – 212 °F]

Operation/Application

Circuit Application	Signal

Industry Standards

Compatible With Approved Standards Products	CSA LR7189, UL E28476
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	2000
Packaging Method	Box

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 281792-5
PLUG HE14 IDC 180 2X5 P AWG 28-26



TE Part # 281839-5
HOUSING HE13 HE14 COSI 2X5 P


Also in the Series | AMPMODU HE 13/HE 14




Connector Contacts(4)




Insertion & Extraction Tools(1)



PCB Headers & Receptacles(51)




Rectangular Connector Housings(17)



Standard Rectangular Connectors(47)




Wire-to-Board Connector Assemblies & Housings(47)



Wire-to-Board Headers & Receptacles (51)

Customers Also Bought




TE Part #281739-6
HEADER HE14 STRAIGHT 2X6 P



TE Part #826652-3
3P AMPMODU II STIFT LEI



TE Part #3-826658-6
36P AMPMODU II STIFT LEI



TE Part #6-966140-4
MESSERLEISTE 9P




TE Part #1-1410297-2
MULTIGIG RT KEY/ESD .8" 45 DEG



TE Part #1-1410297-3
MULTIGIG RT KEY/ESD .8" 90 DEG



TE Part #3-1624112-2
3650 0402 3.9nH 5% 2K RL



TE Part #8-1879263-5
RP 2B 56K2 0.1% 15PPM CUT LENGTH

TE Part #1-6450833-2
MBXLE R/A HDR 7P

TE Part #1-6450872-6
MBXL R/A REC 3ACP + 4P + 24S

Documents

Product Drawings

HEADER HE14 STRAIGHT 2X5 P

English

CAD Files

Customer View Model

ENG_CVM_CVM_281739-5_G.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_281739-5_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_281739-5_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Product Specification

French