322224 ✔ ACTIVE

SOLISTRAND

TE Internal #: 322224

Closed Ring Tongue Terminal, 2/0 AWG, 5/8 / M16 Stud, 15.88 mm [.625 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Uninsulated

View on TE.com >

Terminals & Splices > Ring Terminals



Ring Terminal Product Type: **Closed Ring Tongue Terminal**

Wire Size: **119500 – 150500 CMA**

Stud Size: **5/8, M16**

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	5/8, M16
Sealable	No
Wire Insulation Support Retention Type	Insulation Support

Configuration Features

Number of Holes	2

Body Features

Product Weight	46.748 g

Contact Features

Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin

Mechanical Attachment

Wire Insulation Support	Without

Dimensions

Wire Size	119500 – 150500 CMA
Stud Diameter	15.88 mm[.625 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	68.78 mm[2.708 in]
Barrel Inside Diameter	12.8 mm[.504 in]

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	0 – 170 °C[0 – 338 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

Industry Standards

Government Qualified Terminal	No

Packaging Features

Packaging Quantity	50
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 45439
HYP8/10 SOLIS 2/0AWG DIE SET




TE Part # 1490414-3
HYP10 SOLIS HD 1/0AWG INDENTER



TE Part # 48131
HYP8 SOLIS 1/0-4/0AWG INDENTER



TE Part # 600850
ROTO-CRIMP TOOL (ASI)



TE Part # 48133
HYP8 SOLIS 2/0AWG NEST



TE Part # 1490413-6
HYP10 SOLIS 2/0AWG NEST

Customers Also Bought



TE Part #36916
TERMINAL,SOLIS R 1/0 5/16



TE Part #36919
TERMINAL SOLIS RING 1/0 1/2




TE Part #41729-2
250 FASTON REC 18-16 AWG TPBR



TE Part #CAT-C7901-AL82066
COPALUM Stranded/Solid: Butt Splices



TE Part #320754
TERMINAL,SOLIS R 2 5/8




TE Part #321265
TERMINAL,SOLIS R 4/0 3/8 90DEG



TE Part #321878
TERMINAL,SOLIS R 4/0 3/8



TE Part #322227
TERMINAL,SOLIS R 4/0 5/8



TE Part #2-520272-2
ULTRA-FAST .110/.125 ASY REC 22-18 TPBR

Documents

Product Drawings

TERMINAL,SOLIS R 2/0 5/8

English

CAD Files

Customer View Model

ENG_CVM_CVM_322224_M.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_322224_M.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_322224_M.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English

UL Report

English