36467 ✔ ACTIVE

SOLISTRAND

TE Internal #: 36467

Closed Ring Tongue Terminal, 22 – 16 AWG, #4 / M3 Stud, 3.02 mm [.119 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Uninsulated

View on TE.com >

Terminals & Splices > Ring Terminals






Ring Terminal Product Type: **Closed Ring Tongue Terminal**

Wire Size: **509 – 3260 CMA**

Stud Size: **#4, M3**

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#4, M3
Sealable	No
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Number of Holes	1

Body Features

Product Weight	.414 g

Contact Features

Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin

Mechanical Attachment

Wire Insulation Support	Without

Dimensions

Wire Size	509 – 3260 CMA
Stud Diameter	3.02 mm[.119 in]
Tongue Thickness	.79 mm[.03 in]
Product Length	11.33 mm[.45 in]
Barrel Inside Diameter	1.55 mm[.061 in]

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	0 – 170 °C[0 – 338 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

Industry Standards

Government Qualified Terminal	No

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 49935
DAHT SOLIS 22-10 ASSY



TE Part # 47812
DIES SOLIS 22-16 DIE SET



TE Part # 169400
CERTI-LOK FRAME W/O DIES



TE Part # 58546-1
PC 22-10 SOLISSPICE SPL I SHT



TE Part # 525693
DAHT SOLIS 22-10 ASSY



TE Part # 58545-3
SDE DIE ASSY. 22-10 SOLISTRAND



TE Part # 58545-1
SOLISTRAND 10-22 DIE ASSY

Customers Also Bought



TE Part #2-320862-1
TERMINAL,PIDG SPD FLG 16-14 8



TE Part #320882
PIDG R 22-16 COMM 22-18 MIL 4



TE Part #350737-4
12P UMNL PIN HDR ASSY 94VO LF



TE Part #1-350778-1
02P UMNL V0 CAP HSG BROWN



TE Part #640911-1
RECEPT,PIDG FASTON 22-18 205



TE Part #8-640917-1
RECEPT,PIDG FASTON 22-18 187



TE Part #1-1618239-8
K41A334=RELAY, VACUUM, SPST-NO



TE Part #1-1625873-0
LR0204 LAB-KIT



TE Part #1676285-3
RN 0805 2K21 0.1% 10PPM 5KRL



TE Part #9-1879129-2
RN 0402 2K49 0.1% 10PPM 1K RL

Documents

Product Drawings

SOLIS R 22-16 COMM 22-18 MIL 4

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_36467_J.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_36467_J.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_36467_J.3d_stp.zip

English

3D PDF

English

Customer View Model

ENG_CVM_36467_C.3d_igs.zip

English

Customer View Model

ENG_CVM_36467_C.3d_stp.zip

English

Customer View Model

ENG_CVM_36467_C.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English