380598-2 SUPERSEDED

TE Internal #: 380598-2

TE Internal Description: RCR AU-SPR SN-CUP 018-040

Miniature Spring Sockets: Closed Bottom, Beryllium Copper, 7.5A

View on TE.com >

Connectors > Socket Connectors > Pin Sockets > Miniature Spring Sockets: Closed Bottom, Beryllium Copper, 7.5A



Socket Length: **6.65 mm [.262 in]**

PCB Hole Diameter: **2.26 mm [.089 in]**

Socket Sleeve Style: **Closed Bottom**

Wire Size: **25 – 19 AWG**

All Miniature Spring Sockets: Closed Bottom, Beryllium Copper, 7.5A (9)

Features

Product Type Features

Connector & Contact Terminates To	Printed Circuit Board
Socket Sleeve Style	Closed Bottom
Connector System	Cable-to-Board
Sealable	No

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire

Body Features

Sleeve Plating Material	Tin
Sleeve Material	Copper

Contact Features

Contact Spring Plating Material	Gold
Contact Base Material	Beryllium Copper
Contact Mating Area Plating Material Thickness	30 µm[30 µin]
Contact Spring Plating Thickness	.762 µm[30 µin]
Contact Current Rating (Max)	7.5 A

Termination Features

Termination Method to PCB	Through Hole - Press-Fit
Termination Method to Wire & Cable	Solder

Insertion Method	Hand/Semi-Automatic

Dimensions

PCB Thickness (Recommended)	.79 – 3.18 mm[.031 – .125 in]
Socket Length	6.65 mm[.262 in]
PCB Hole Diameter	2.26 mm[.089 in]
Wire Size	25 – 19 AWG
Mating Pin Diameter Range	.46 – 1.02 mm[.018 – .04 in]

Operation/Application

Circuit Application	Power & Signal

Packaging Features

Packaging Method	Bag, Loose Piece
Packaging Quantity	2000

Other

Spring Material	Beryllium Copper

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Pb (13% in Component part) **Article Safe Usage Statements:** Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Pin-in-Paste capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these

limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought




TE Part #35247
TERMINAL,SOLIS R 8 1/4



TE Part #640389-3
03P MTA156 HDR ASSY SQ R/A F/L



TE Part #5-747905-2
9 Rcpt Solder Cup, Gold Flash,



TE Part #1419106-1
27E006=SOCKET,KH,14,SLG,G/T,PH



TE Part #102448-8
20 AMPMODU MT ASSY DR .100CL

Documents

Product Drawings

RCR AU-SPR SN-CUP 018-040

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_380598-2_AF.2d_dxf.zip

English

Customer View Model

ENG_CVM_380598-2_AF.3d_igs.zip

English

Customer View Model

ENG_CVM_380598-2_AF.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Reusable Receptacles For Component Testing

English