
DRAWING MADE IN THIRD ANGLE PROJECTION

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION ,19 .
© COPYRIGHT 19 BY AMP INCORPORATED. ALL INTERNATIONAL RIGHTS RESERVED.

LOC	DIST	P	F
G	14		

REVISIONS

ZONE	LTR	DESCRIPTION	DATE	APPD
	D	REV,RDRW,& SM PKG PER 0720-0040-93	4-5-93	TAB DAP



METRIC

DIMENSIONS LISTED IN mm [INCHES]

AMP WIRE RANGE	UL Listed
4 AWG SOLID OR STRANDED	4 AWG STRANDED

CSA LR7189 Certified	MILITARY P/N AND CLASS
4 AWG SOLID OR STRANDED	NOT APPLICABLE

1. STAMP AMP 4W* APPROX AS SHOWN
2. MAXIMUM LENGTH DOES NOT INCLUDE MANUFACTURING TABS

QUANTITY	PACKAGE TYPE	PART NO
25	LOOSE PIECE, BAG	8-34323-5
25	LOOSE PIECE, BOX	8-34323-3
----	LOOSE PIECE	34323

34323

AMP INCORPORATED CUSTOMER SERVICE SYSTEMS

FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1-800-722-1111
FOR ORDER ENTRY	1-800-526-5142

MAX RECOMMENDED OPERATING TEMPERATURE: 170°C MAX

VOLTAGE RATING: NOT APPLICABLE

WIRE CROSS SECTIONAL AREA RANGE: 16.8-26.7mm² [33,100-52,600] CIR MILS SOLID OR STRANDED

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

DO NOT SCALE PRINT.
UNLESS SPECIFIED ~~DIMENSIONS IN mm [INCHES]~~
TOLERANCES ON :
2 PLC DEC ± -
3 PLC DEC ± -
ANGLES ± -

MATERIAL: COPPER PER ASTM B-152 ANNEALED

FINISH: TIN PLATE 0.00254[.000100] MIN THK PER MIL-T-10727

DR 4-5-93 TA BRINKMAN
CHK 4-5-93 DA PATTERSON
APPD 4-5-93 DE MILLER
APPD 4-5-93 JL MECKLEY
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT _

AMP Incorporated
Harrisburg, PA 17105-3608

NAME: SPLICE, BUTT, STANDARD, SOLISTRAND™

SIZE	CAGE CODE	DRAWING NO
C	00779	C-34323

SCALE 8:1 SHEET 1 OF 1

CUSTOMER DRAWING

AMP 1471-6 REV 3-92

10 SEP 1993 15:13:54 AMP26463 <US128A>DEPT1123>DWG1123>U.SOLISTRAND>U.BUTT-SPLICE