963827-3 ✔ ACTIVE


FASTIN-FASTON | FASTIN-FASTON 375

TE Internal #: 963827-3

Quick Disconnect Receptacle, Uninsulated, 17 – 13 AWG, 1.03 – 2.62 mm² Wire, 9.53 mm [.375 in] Tab Width, F-Crimp, Straight, FASTIN-FASTON 375

View on TE.com >

Terminals & Splices > Quick Disconnects




Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **1.03 – 2.62 mm²**

Mating Tab Width: **9.53 mm [.375 in]**

Mating Tab Thickness: **1 mm [.039 in]**

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	9.53 mm[.375 in]
Mating Tab Thickness	1 mm[.039 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Locking Lance Height	1.9 mm[.074 in]
Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Product Length	27 mm[1.063 in]
Compatible Insulation Diameter Range	2.4 – 3.7 mm[.094 – .145 in]
Terminal Material Thickness	.51 mm[.02 in]
Wire Size	1.03 – 2.62 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	500
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits


as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2385411-1
SDE F SERIE 9.5 1.5-2.5 ASSY

Also in the Series | FASTIN-FASTON 375



Crimp Terminal Housings(7)



Insertion & Extraction Tools(1)




Quick Disconnects(16)

Customers Also Bought



TE Part #K1158495
Plunger Switch 44-01-044 900



TE Part #5-160446-6
FF 250 REC 1.0-2.5MM2 BR SILVER PLATED



TE Part #160450-3
FF 250 TAB 18-14AWG PB SILVER PL



TE Part #CAT-T4827-T273
TIMER, RECEPTACLE AND TAB



TE Part #928193-1
FF 2.8MM TAB HSG 2P PBT BLACK



TE Part #928930-1
FF 110 TAB 0.5-1 MM2 .080 F SSP CUZN30



TE Part #953381-1
LOCKING DEVICE FOR 6W MQS



TE Part #1703810-1
SLIDE,TAB HSG GROUP B

Documents

Product Drawings

FF STECKHUELSE 9,5

German

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_963827-3_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_963827-3_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_963827-3_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

German