DX1091/YL Datasheet

Product Name // 5mm LED Indicator DX1091 Series Recessed Profile Anodised Aluminium Bezel IP66 Sealed Yellow LED

View Product Page



Image not found or type unknown

// Product Description:

- 5mm LED Indicators
- Choice of profile, depending on part code prefix:
- DX0998, DX1120, DX1090, DX1091: Recessed profile
- DX0999, DX1121, DX1092, DX1093: Prominent profile
- Choice of Bezel material, depending on part code prefix:
- DX0998, DX0999: Chrome Plated Brass
- DX1120, DX1121: Glass Filled Nylon
- DX1091, DX1093: Anodised Aluminium
- DX1090, DX1092: Black Anodised Aluminium
- All Aluminium bodied parts are IP66 Front Panel Sealed
- Choice of Illumination colour depending on part code:
- Single colour LED: /RD - Red, /GN - Green, /YL - Yellow, /BL - Blue
- Dual colour LED: /D1 - Red/Green, /D2 - Red/Amber, /D3 - Green/Amber
- Tri-colour LED: /TR - Red/Green/Amber
- Flashing LED: /RD/02 - Red, /GN/02 - Green
- No resistor installed; see data for ratings to enable calculation of suitable series resistor value for application

// General Information:

Product Display Title:	5mm LED Indicators
Product Family:	Indicators
Product Series:	5mm LED Indicators
Change Notes:	MK-012354-SL
Body Material:	Aluminium Clear Anodised
Current Max:	0.03A
Diameter:	10.3mm
Function:	LED Indicator
Illumination Colour:	Yellow
Illumination Shape:	Dot
Illumination Style:	Illuminated
Illumination Voltage:	No Resistor
Indicator Profile:	Recessed Profile
Ip Rating:	IP66
Max Operating Temperature:	+85°C
Min Operating Temperature:	-40°C
Thread Size:	0.312 inch x 32TPI
Voltage Max:	2.1V

// Product PDF Links

Indicators product data

// Product 3D CAD Model Links

DX1091/YL3D CAD Model