**Part Number :** 1731120576
**Product Description :** FCT Coaxial Contact, Male, Straight, Crimp, 75 Ohms, 0.20µm Gold Plating, for RG-179BU or RG-187AU Cable
**Series Number :** 173112
**Status :** Active
**Product Category :** D-Sub Contacts
**Engineering Part Number :** FMS002P101



## Documents and Resources

### Drawings

1731120576_sd.pdf

STEP AP242

SOLIDWORKS

Creo

### Specifications

2195600660-000.pdf

1731120009-PK-000.pdf

2195600660-000.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Contains Lead; pyrochlore, antimony lead yellow per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | D-Sub Contacts |
| Series | 173112 |
| Description | FCT Coaxial Contact, Male, Straight, Crimp, 75 Ohms, 0.20µm Gold Plating, for RG-179BU or RG-187AU Cable |
| Contact Type | Coaxial |
| Magnetic | Yes |
| Product Name | FCT Products |
| Type | Mixed Layout |
| UPC | 191128317627 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 2.0A |
| Impedance | 75Ω |

### Physical

| | |
|---|---|
| Durability (mating cycles min) | 200 |
| Gender | Male |

| | |
|---|---|
| Material - Contact | Copper Alloy |
| Material - Plating Mating | Gold over Nickel |
| Material - Plating Termination | Tin over Nickel |
| Net Weight | 1.600/g |
| Orientation | Straight |
| Packaging Type | Bag |
| Plating min - Mating | 0.200µm |
| Plating min - Termination | 5.000µm |
| Temperature Range - Operating | -55° to +135°C |
| Termination Style | Crimp |
| Wire/Cable Type | RG-179BU, RG-187AU |

## Mates With / Use With

### Use with Part(s)

| Description | Part Number |
|---|---|
| Use With | FCT Mixed Layout Connectors |

---

## Application Tooling

## Global

| Description | Part Number |
|---|---|
| FCT Hand Crimp Tool, Mini Frame, 8-Step Adjust | 1731121730 |
| FCT Hand Crimp Tool, Hex Die, Open Frame | 1731121732 |
| FCT Locator for Size 8 Contacts, Coax | 1731121738 |
| FCT Removal Tool for Size 8 Contacts | 1731121747 |

---