**Part Number :** 191640018
**Product Description :** Perma-Seal Female Quick Disconnect Receptacle for 22-18 AWG Wire, Tab Size 6.35 x 0.81mm, Mylar Tape Carrier
**Series Number :** 19164
**Status :** Active
**Product Category :** Quick Disconnects
**Engineering Number :** SAA-9261T



## Documents & Resources

### Drawings

191640018_sd.pdf

### Specifications

PS-19902-015-001.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Quick Disconnects |
| Series | 19164 |
| Description | Perma-Seal Female Quick Disconnect Receptacle for 22-18 AWG Wire, Tab Size 6.35 x 0.81mm, Mylar Tape Carrier |
| Product Name | Perma-Seal |
| Type | Standard Quick Disconnect |
| UPC | 800753113060 |

### Agency

| | |
|---|---|
| CSA | LR18689 |
| UL | E79133 |

### Electrical

| | |
|---|---|
| Voltage - Maximum | 600V |

### Physical

| | |
|---|---|
| Barrel Type | Closed |
| Color - Resin | Red |
| Gender | Female |
| Glow-Wire Capable | No |
| Insulated | Fully |
| Insulation | NiAc |
| Lock to Mating Part | None |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |

| | |
|---|---|
| Material - Plating Termination | Tin |
| Material - Resin | Nylon |
| Net Weight | 1.733/g |
| Orientation | Straight |
| Packaging Type | Adhesive Tape on Reel |
| Plating min - Mating | 2.540µm |
| Plating min - Termination | 2.540µm |
| Tab Thickness | 0.81mm |
| Tab Width | 6.35mm |
| Temperature Range - Operating | -55° to +125°C |
| Wire Insulation Diameter | 4.32mm max. |
| Wire Size (AWG) | 18, 20, 22 |

## Application Tooling

## Global

| Description | Part Number |
|---|---|
| ATP Crimp Dies for the Tape Crimp Module and ATP-101 & 301 Press | 192880095 |