
molex



**Part Number :** 2025694105
**Product Description :** Ultra-Fit Plug Housing, 3.50mm Pitch, Single Row, 5 Circuits, Panel Mount, Natural, Glow-Wire Capable
**Series Number :** 202569
**Status :** Active
**Product Category :** Connector Housings

## Documents & Resources

### Drawings

2025694105_sd.pdf

2025691000-PK-000.pdf

### 3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

### Specifications

1723230003-000.pdf

2169461000-PS-000.pdf

2169460001-TS-000.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Connector Housings |
| Series | 202569 |
| Description | Ultra-Fit Plug Housing, 3.50mm Pitch, Single Row, 5 Circuits, Panel Mount, Natural, Glow-Wire Capable |
| Application | Power, Wire-to-Wire |
| Product Name | Ultra-Fit |
| UPC | 195842152564 |

### Agency

| | |
|---|---|
| UL | E29179 |

### Physical

| | |
|---|---|
| Circuits (maximum) | 5 |
| Color - Resin | Natural |
| Flammability | 94V-0 |
| Gender | Plug |
| Glow-Wire Capable | Yes |
| Keying to Mating Part | Yes |

| | |
|---|---|
| Lock to Mating Part | Yes |
| Material - Resin | Polyamide |
| Net Weight | 2.000/g |
| Number of Rows | 1 |
| Packaging Type | Bag |
| Panel Mount | Yes |
| Pitch - Mating Interface | 3.50mm |
| Pitch - Termination Interface | 3.50mm |
| Polarized to Mating Part | Yes |
| Temperature Range - Operating | -40° to +125°C, -40° to +120°C |

## Mates With / Use With

### Mates with Part(s)

| Description | Part Number |
|---|---|
| Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 5 Circuits, Natural, Glow-Wire Capable | 1722564105 |

### Use with Part(s)

| Description | Part Number |
|---|---|
| Ultra-Fit Tangless Terminal Position Assurance (TPA), 3.50mm Pitch, 5 Circuits, Black | 1722643005 |
| Ultra-Fit Male Crimp Terminals | 216946 |