**Part Number :** 2065600200
**Product Description :** 1558MHz-1610MHz GNSS Flex Antenna, 200.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors
**Series Number :** 206560
**Status :** Active
**Product Category :** Antennas



## Documents & Resources

### Drawings

2065600200_sd.pdf

2065600050-001.pdf

### 3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

### Specifications

2065600050-AS.pdf

2065600050-PS.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS

- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Antennas |
| Series | 206560 |
| Description | 1558MHz-1610MHz GNSS Flex Antenna, 200.00mm Cable Length, Compatible with U.FL / I-PEX MHF Connectors |
| Component Type | Flexible Antenna with Cable |
| Function | Signal |
| Product Name | 1558MHz-1610MHz GNSS Flexible |
| Protocol | BeiDou, GLONASS, GPS |
| Type | GNSS Antenna, Internal |
| UPC | 191128769136 |

### Electrical

| | |
|---|---|
| Band#1 F_End (MHz) | 1564 |
| Band#1 F_Start (MHz) | 1558 |
| Band#2 F_End (MHz) | 1578 |
| Band#2 F_Start (MHz) | 1572 |
| Band#3 F_End (MHz) | 1605 |
| Band#3 F_Start (MHz) | 1599 |
| Electrical Connectivity | Cable |

| | |
|---|---|
| Peak Gain (dBi) | 0.7 @ 1561 MHz, 0.8 @ 1575 MHz, 1.1 @ 1602 MHz |
| Return Loss - S11 (dB) | < -8 |
| Total Efficiency | >68% @ 1575 MHz, >68% @ 1561 MHz, >69% @ 1602 MHz |

### Physical

| | |
|---|---|
| Cable Length | 200.00mm |
| Length | 40.40mm |
| Mounting Style | Adhesive |
| Net Weight | 0.847/g |
| Packaging Type | PET Film |
| Polarization | Linear |
| Radiation Pattern | Omnidirectional |
| Thickness | 0.10mm |
| Width | 15.40mm |

## Mates With / Use With

### Mates with Part(s)

| Description | Part Number |
|---|---|
| MCRF Jack, Straight, PCB Receptacle, Surface Mount, 1.25mm Mounted Height, 50 Ohms | 734120110 |