Part Number: 34763-0008

Image not available

Series image - Reference only

Status:	Contact Molex
Series:	34763
Category:	PCB Headers
Overview:	CMC and CMX Sealed, Hybrid, Modular Connectors

CHECK DISTRIBUTOR INVENTORY

Add to My Parts

Email this page

Go to Part Detail▼

Specifications & Other Documents:

Note - Please disable browser pop-up blockers to view documents on www.molex.com

Product Environmental Compliance

Questions on Product Environmental Compliance? Email productcompliance@molex.com

EU ELV: Compliant
EU RoHS: Compliant
China RoHS:
REACH SVHC: Contains SVHC(2014 December 17): No
Low-Halogen Status: Not Relevant

RoHS Certificate of Compliance (PDF)

Multiple Part Product Compliance Form

Application Tooling

FAQ

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
154 Way CMC Header Assembly PCB Insertion Fixture	62203-0500

Previously Available Application Tooling

Check our list of old tooling that used to be available for this part

Part Detail

COLLAPSE ALL

General

Status	Contact Molex
Category	PCB Headers
Series	34763
Application	Board-to-Board, Wire-to-Board
Application Tooling Part Link	62203-0500
Overview	CMC and CMX Sealed, Hybrid, Modular Connectors
Product Name	CMC
UPC	884982161924

Physical

Breakaway	No
Circuits (Loaded)	154
Circuits (maximum)	154
Color - Resin	Black, Brown, Gray
First Mate / Last Break	No
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Plating Mating	Tin
Material - Resin	Nylon Alloy
Net Weight	119.264/g
Number of Rows	4
Orientation	Right Angle
Packaging Type	Tray
Pitch - Mating Interface	2.50mm, 3.50mm, 3.70mm, 4.00mm, 4.50mm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Through Hole - Compliant Pin

Electrical

(Please review the Product Specification for specific details.)	
Current - Maximum per Contact	10.5A, 13.5A, 17.0A, 8.0A
Voltage - Maximum	250V AC

Solder Process Data

Lead-freeProcess Capability	N/A

Material Info

Reference - Drawing Numbers

Application Specification	AS-34763-001
Product Specification	PS-34763-001
Sales Drawing	SD-34763-001

Copyright 2015