**Part Number :** 532591329
**Product Description :** Mighty-SPOX Header, 3.50mm Pitch, Right-Angle, 13 Circuits, Brass (CuZn) Contact
**Series Number :** 53259
**Status :** Obsolete
**Product Category :** PCB Headers and Receptacles



Obsolete

## Documents & Resources

### Drawings

532591329_sd.pdf

### 3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

Symbol and Footprint (Multi-Format)

### Specifications

SPK-53259-001-001.pdf

PS-51067-019-001.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Compliant with Exemption 44; 33 |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Obsolete |
| Category | PCB Headers and Receptacles |
| Series | 53259 |
| Description | Mighty-SPOX Header, 3.50mm Pitch, Right-Angle, 13 Circuits, Brass (CuZn) Contact |
| Application | Power, Wire-to-Board |
| Component Type | PCB Header |
| Product Name | Mighty-SPOX |
| UPC | 822348135486 |

### Agency

| | |
|---|---|
| CSA | LR19980 |
| UL | E29179 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 5.5A |
| Voltage - Maximum | 250V |

### Physical

| | |
|---|---|
| Breakaway | No |

Obsolete

| | |
|---|---|
| Circuits (Loaded) | 13 |
| Circuits (maximum) | 13 |
| Durability (mating cycles max) | 30 |
| First Mate / Last Break | No |
| Flammability | 94V-0 |
| Glow-Wire Capable | No |
| Guide to Mating Part | Yes |
| Keying to Mating Part | Yes |
| Lock to Mating Part | Yes |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Net Weight | 3536.500/mg |
| Number of Rows | 1 |
| Orientation | Right Angle |
| Packaging Type | Tray |
| PCB Locator | Yes |
| PCB Retention | None |
| PCB Thickness - Recommended | 1.60mm |
| PC Tail Length | 3.50mm |
| Pitch - Mating Interface | 3.50mm |
| Plating min - Termination | 1.000µm |
| Polarized to PCB | Yes |
| Shrouded | Fully |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C |
| Termination Interface Style | Through Hole |

Obsolete

## Mates With / Use With

### Mates with Part(s)

| Description | Part Number |
|---|---|
| Mighty-SPOX Female Crimp Terminals | 50217 |
| Mighty-SPOX Receptacle Housings | 51067 |

Obsolete