
**Part Number :** 733910083
**Product Description :** SMA Jack, Right-Angle, PCB Receptacle, Through Hole, Die Cast Body, Gold (Au) Plated, 3.43mm Leg Length, 80 Pieces Per Tray, 50 Ohms
**Series Number :** 73391
**Status :** Active
**Product Category :** RF / Coaxial Connectors



## Documents & Resources

### Drawings

733910083_sd.pdf

### 3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

Symbol and Footprint (Multi-Format)

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | RF / Coaxial Connectors |
| Series | 73391 |
| Description | SMA Jack, Right-Angle, PCB Receptacle, Through Hole, Die Cast Body, Gold (Au) Plated, 3.43mm Leg Length, 80 Pieces Per Tray, 50 Ohms |
| Application | RF |
| Product Name | SMA |
| Style | PCB |
| Type | Subminiature |
| UPC | 884982395084 |

### Electrical

| | |
|---|---|
| Frequency | 18 GHz |
| Impedance | 50Ω |
| Power / Voltage | VOLTAGE: 500 Vrms@Sea Level |

### Physical

| | |
|---|---|
| Cable Attachment | N/A |
| Gender | Jack |
| Keying to Mating Part | N/A |
| Net Weight | 2.890/g |

| | |
|---|---|
| Orientation | Right Angle |
| Packaging Type | Tray |
| Panel Mount | No |
| Panel Mount Method | N/A |
| PCB Mounting | Through Hole |
| PCB Thickness - Recommended | 3.31mm |
| Reverse Polar | No |
| Wire/Cable Type | N/A |

**Solder Process Data**

| | |
|---|---|
| Max-Duration | 10 |
| Lead-Free Process Capability | SMC&WAVE |
| Max-Cycle | 2 |
| Max-Temp | 260 |