
Potentiometers

Molded composition

Ohmite molded composition potentiometers are available in various models for applications in military devices, industrial equipment and in equipment requiring a convenient resistance control device.

FEATURES

- Low noise, smooth operation
- In accordance with "Mil" RV4N, RV4L, RV6L, RV6N, 2RV7N types
- RoHS compliant; non-RoHS version unavailable.



February 2021:
Select parts have been discontinued.
Please refer to the ordering information below.

SERIES SPECIFICATIONS

Model	Watts	Ohmic range	Behind panel (in./mm)	Diameter (in./mm)	Rotation	Voltage (RMS)
AS	0.5	50-5M	0.703/17.9	0.50/12.7	295° ±5°	350
ASM	0.5	50-5M	0.703/17.9	0.50/12.7	295° ±5°	350
CA	2.0	50-5M	0.625/15.9	1.16/29.4	312° ±3°	500
CB	2.0	50-5M	0.625/15.9	1.16/29.4	312° ±3°	500
CU	2.0	50-5M	0.625/15.9	1.16/29.4	312° ±3°	500
CCU	2.0	50-5M	1.266/32.1	1.16/29.4	312° ±3°	500
CLU	2.0	50-5M	0.625/15.9	1.16/29.4	312° ±3°	500
CMU	2.0	50-5M	0.625/15.9	1.16/29.4	312° ±3°	500

CHARACTERISTICS

Derating	linear from 100% at +70°C to 0% at +120°C
Operating temp. range	-55°C to 120°C
Construction	Elements molded into a single, integral structure. Metal cover protects and shields the internal parts.
Sealing	synthetic resin containing non-mercurial fungicide
Product life	Since all rheostats/potentiometers are electro-mechanical devices, they are subject to mechanical wear and, therefore, have a finite life.


(continued)

Potentiometers

Molded composition

DIMENSIONS

(iin./mm)



Model	Watts	Behind panel	Diameter	Rotation
AS	0.5	0.703/17.9	0.50/12.7	295° ±5°
ASM	0.5	0.703/17.9	0.50/12.7	295° ±5°
CA	2.0	0.625/15.9	1.16/29.4	312° ±3°
CB	2.0	0.625/15.9	1.16/29.4	312° ±3°
CU	2.0	0.625/15.9	1.16/29.4	312° ±3°
CCU	2.0	1.266/32.1	1.16/29.4	312° ±3°
CLU	2.0	0.625/15.9	1.16/29.4	312° ±3°
CMU	2.0	0.625/15.9	1.16/29.4	312° ±3°

ORDERING INFORMATION

Ohmic value	MIL Designation Prefix ➤ Suffix ▼	Part No. Prefix ➤ Suffix ▼	CMU RV4NAYSD Linear	CU RV4NAYSJ Linear	CA RV4NAYSJ CW log	CB RV4NAYSJ CCW log	CLU RV4LAYSA Linear	CCU 2RV7NYSJ Linear Dual*	RV6LAYSA Linear	RV6NAYSD Linear
50	500A	5001	✖	✖			✖			
100	101A	1011	✔	✔			✖		✖ **AS**3601E	✖ **ASM**6661E
150	151A	1511	✖	✖			✖			
250	251A	2511	✖	✔			✖		✖ **AS**3602E	✖ **ASM**6662E
350	351A	3511	✖	✖			✖			
500	501A	5011	✖	✔			✖		✖ **AS**3603E	✖ **ASM**6663E
750	751A	7511	✖	✖			✖			
1,000	102A	1021	✔	✔			✖		✖ **AS**3604E	✖ **ASM**6664E
1,500	152A	1521	✔	✖			✔			
2,500	252A	2521	✔	✔			✔		✖ **AS**3605E	✖ **ASM**6665E
3,500	352A	3521	✖	✖			✖			
5,000	502A	5021	✔	✔			✔		✖ **AS**3606E	✖ **ASM**6666E
7,500	752A	7521	✖	✖			✖			
10,000	103A	1031	✔	✔		✔	✔	✔	✖ **AS**3607E	✔ **ASM**6667E
15,000	153A	1531	✖	✖			✖			
25,000	253A	2531	✔	✔		✔	✔	✖	✖ **AS**3608E	✖ **ASM**6668E
35,000	353A	3531	✔	✖			✔			

Ohmic value	MIL Designation Prefix ➤ Suffix ▼	Part No. Prefix ➤ Suffix ▼	CMU RV4NAYSD Linear	CU RV4NAYSJ Linear	CA RV4NAYSJ CW log	CB RV4NAYSJ CCW log	CLU RV4LAYSA Linear	CCU 2RV7NYSJ Linear Dual*	RV6LAYSA Linear	RV6NAYSD Linear
50,000	503A	5031	✖	✖		✔	✖	✖	✖ **AS**3609E	✖ **ASM**6669E
75,000	753A	7531	✖	✖			✖			
100,000	104A	1041	✖	✖	✔		✔	✖	✖ **AS**3610E	✖ **ASM**6670E
150,000	154A	1541	✖	✖			✖			
250,000	254A	2541	✔	✖	✖		✔	✖	✖ **AS**3611E	✖ **ASM**6671E
350,000	354A	3541	✖	✖			✖			
500,000	504A	5041	✔	✖	✖		✔	✖	✖ **AS**3612E	✖ **ASM**6672E
750,000	754B	7542	✖	✖			✖			
1,000,000	105B	1052	✖	✖	✖		✖	✖	✖ **AS**3613E	✖ **ASM**6673E
1,500,000	155B	1552	✖	✖			✖			
2,000,000	205B	2052	✖	✖			✖		✖ **AS**3684E	✖ **ASM**6674E
2,500,000	255B	2552	✖	✖	✔		✖			✖ **ASM**6675E
3,500,000	355B	3552	✖	✖			✖			
5,000,000	505B	5052	✖	✖			✖		✖ **AS**3615E	✖ **ASM**6676E

✔ = Standard values; check availability
✖ = Discontinued
* add "-E" for RoHS-compliant lead-free zinc-nickel plated product