2-1904058-7 ✔ ACTIVE

EVC | Mini K HV Precharge Relay

TE Internal #: 2-1904058-7

High Voltage Relay, DC, Monostable, 1 Form X SPST-NO-DM, 20 A Contact Rating, 12 VDC Coil Voltage, 400 VDC Contact Voltage, Mini K HV Precharge Relay

View on TE.com >

Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **High Voltage Relay**

Coil Magnetic System: **Monostable**

Contact Arrangement: **1 Form X SPST-NO-DM**

Current Type: **DC**

Contact Current Rating: **20 A**

Features

Product Type Features

Relay & Contactor Type	High Voltage Relay

Configuration Features

Coil Special Features	Resistor in Parallel
Contact Arrangement	1 Form X SPST-NO-DM

Electrical Characteristics

Contact Limiting Making Current	20 A
Contact Limiting Breaking Current	20 A
Insulation Initial Dielectric Between Open Contacts	2000 Vrms
Contact Current Rating	20 A
Coil Voltage Rating	12 VDC
Contact Switching Voltage (Max)	450 VDC
Contact Voltage Rating	400 VDC
Coil Resistance	41.6 Ω
Coil Power Rating DC	3.5 W
Insulation Initial Dielectric Between Contacts & Coil	2000 Vrms

Body Features

Product Weight	39 g[1.376 oz]

Enclosure Type	Flux Resistant Automatic Solder Capable & Washable

Contact Features

Contact Material	Silver Alloy

Termination Features

Main Termination & Connection Type	Quick Connect Terminals
Coil Termination & Connection Type	Quick Connect Terminals

Mechanical Attachment

Product Mount Type	Socket Mount

Dimensions

Product Width	36.6 mm[1.441 in]
Product Length	29.9 mm[1.177 in]
Product Height	29.9 mm[1.177 in]

Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
Environmental Category of Protection	RTIII
Environmental Ambient Temperature (Max)	85 °C[185 °F]

Operation/Application

Coil Magnetic System	Monostable
Current Type	DC

Other

Contact Current Class	>16 – ≤25 A
Coil Power Rating Class	>3 – ≤10 W
Height Class (Mechanical)	>27 – ≤33 mm[>1.063 – ≤1.299 in]
Length Class (Mechanical)	>22 – ≤33 mm[>.866 – ≤1.299 in]
Width Class (Mechanical)	>33 mm[>1.299 in]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold

EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 2-1904058-5
Mini-K HV PCB

Also in the Series | Mini K HV Precharge Relay



Automotive Relays(2)



DC Relays(2)



High Voltage Relays(2)




PCB Relays(1)

Customers Also Bought



TE Part #YHV280-2PM-S-4MM-A
HVA280-2PHM,SHUNTED,4SQMM, KEY A



TE Part #966871-1
MOD2 ST-WANNE 2X10P



TE Part #1-1393779-8
V23101D 7A201



TE Part #1564411-6
SLIDE,TAB HSG GROUP E



TE Part #4-1625890-3
2W SM M/OX 5% 33R




TE Part #2-1625971-0
HSA25 1R2 5%




TE Part #1703806-1
ADAPTER,SEALED,ASSY



TE Part #2112166-2
SLIDE,FOR 21POS.



TE Part #1-2394804-1
4POS,TAB0.5X0.4,HDR ASSY,180DEG, COD A



TE Part #1-2395006-1
12POS,TAB0.5X0.4,HDR ASSY, 180DEG,COD A

Documents

Product Drawings

Mini-K HV Plug-In

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1904058-7_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1904058-7_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1904058-7_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

High Voltage Relays & Contactors, High Voltage Relay, Mini K HV Precharge Relay

English

Product Specifications

Definitions General Purpose Relays

English