S200-4-01-100HN ✔ ACTIVE

RAYCHEM

TE Internal #: C69495-000

5.97 mm [.235 in] Expanded Inside, Shrinks To 3.3 mm [.13 in], Pre-Installed Lead, SolderSleeve Shield Terminators

View on TE.com >

Wire Protection & Management > Interconnect Devices > SolderSleeve Shield Terminators



Operating Temperature (Max): **200 °C [392 °F]**

Expanded Inside Diameter (Min): **5.97 mm [.235 in]**

Recovered Inside Diameter (Max): **3.3 mm [.13 in]**

Pre-Installed Lead: **Yes**

Resistance Properties: **Immersion Protection**

Features

Product Type Features

Temperature Indicator	Yes
Interconnect Device Splice Type	Shield Terminator
Temperature Indicator Type	Fusible Ring

Configuration Features

Pre-Installed Lead Type	Braid
Pre-Installed Lead	Yes

Body Features

Lead Plating Material	Nickel
Lead Color	Braid

Dimensions

Compatible Jacket Diameter Range	5.95 mm[.234 in]
Product Length	19.1 mm[.75 in]
Shield Outside Diameter (Min)	3.3 mm[.13 in]
Pre-Installed Lead Wire Size	640 CMA
Dielectric Outside Diameter (Max)	5.95 mm[.234 in]
Expanded Inside Diameter (Min)	5.97 mm[.235 in]
Recovered Inside Diameter (Max)	3.3 mm[.13 in]

Usage Conditions

Operating Temperature (Max)	200 °C[392 °F]
Resistance Properties	Immersion Protection
Wire Temperature (Max)	150 °C

Industry Standards

Government Qualified	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # EG8162-000
HL1920E-230V-EURO


Customers Also Bought




TE Part #CAT-AS22759-32
SAE AS22759: 32/33/44/45/46 - Single-Wall, Lightweight Wire



TE Part #2562-201-2031L
CONT SOC ASSY



TE Part #462673-000
55A0121-22-9/96CS2275



TE Part #819097-000
381A302-51-0



TE Part #5-103957-9
2X10 MTE RCPT SR LATCH .100CL



TE Part #205170-1
AMPLIMITE,ASY,PLUG,STD,109,5



TE Part #746610-8
034 DIP PLUG 100CL TIN

Documents

Product Drawings

S200-4-01-100HN

English

Datasheets & Catalog Pages

Raychem S200 Shield Terminators

English