X2-2.5-0-SP-SM ✔ ACTIVE


RAYCHEM | RAYCHEM SWFR X2

TE Internal #: EM7482-000

Heat Shrink Tubing, Black, 2:1, Single Wall, Shrinks To 1.25 mm [.049 in], ZEROHAL Polyolefin, 2.9 mm [.114 in] Expanded Inside, RAYCHEM SWFR X2

View on TE.com >

Heat Shrink Tubing > SWFR-X2 Heat Shrink Tubing





Tubing Product Type: **Heat Shrink Tubing**

Primary Product Color: **Black**

Wall Type: **Single Wall**

Expanded Inside Diameter (Min): **2.9 mm [.114 in]**

Recovered Inside Diameter (Max): **1.25 mm [.049 in]**

All SWFR-X2 Heat Shrink Tubing (21)

Features

Product Type Features

Tubing Product Type	Heat Shrink Tubing
Wall Type	Single Wall

Electrical Characteristics

Operating Voltage (Max)	.6 kV

Body Features

Fluid Type	Water
Primary Product Color	Black
Shrink Ratio	2:1
Primary Product Material	ZEROHAL Polyolefin
Flexibility	Very Flexible

Dimensions

Recovered Wall Thickness (Nominal)	.44 mm[.017 in]
Expanded Inside Diameter (Min)	2.9 mm[.114 in]
Recovered Inside Diameter (Max)	1.25 mm[.049 in]

Usage Conditions

Shrink Temperature (Min)	70 °C
Tubing Flammability Type	Flame-Retardant
Operating Temperature Range	-30 – 125 °C[-22 – 257 °F]
Recovery Temperature	90 °C

Operation/Application

Mechanical Resistance	Abrasion

Product Availability

Applicable Region	Global

Packaging Features

Packaging Method	Spool

Other

Meets Low Outgassing Requirements	No
Product Source	China

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides


on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # EG1114-000
CV1981-ST-230V1600W-EU

Also in the Series | RAYCHEM SWFR X2



Heat Shrink Tubing(22)




Single Wall Tubing(22)

Customers Also Bought



TE Part #0460-204-12141
PIN, SOLID, SIZE 12, 12-14AWG, NI




TE Part #2820123007
44A0111-18-2



TE Part #DTP04-2P
REC, 2P, GRY, N



TE Part #WP-2P
WEDGE LOCK, 2P, REC, ORG, DTP



TE Part #EM7481-000
X2-2.0-0-SP-SM



TE Part #1-640454-0
10P MTA100 HDR ASSY SQ STR POL




TE Part #7-1393246-2
W23-X1A1G-35=W23/W31



TE Part #7-1393246-4
W23-X1A1G-40=W23/W31



TE Part #7-1393246-6
W23-X1A1G-50=W23/W31



TE Part #2040852-1
SHIELD FINGER 0820 N-B WITH SE

Documents

Product Drawings

X2-2.5-0-SP-SM

English

X2-2.5-0-SP-SM

English

Datasheets & Catalog Pages

Highly Flame-Retardant, Zero halogen, Low Recovery Temperature, Metric-Sized Heat-Shrinkable Tubing

English

Product Specifications

Application Specification

English