
TIGER BUY™ CONTACT

ELEVATED SOCKETS



(2.54 mm) .100" PITCH • ESW/ESQ SERIES

ESW/ESQ

Mates:
TSW, MTSW, EW, MTLW, TSS, ZSS, TSM, DW, ZW, HW, TSSH, HTSS

SPECIFICATIONS

Insulator Material:
Black Glass Filled Polyester
Contact Material:
Phosphor Bronze
Plating:
Au or Sn over
50 µ" (1.27 µm) Ni
Operating Temp Range:
-55 °C to +125 °C with Gold
-55 °C to +105 °C with Tin
Current Rating (ESW/TSW):
5.2 A per pin
(2 pins powered)
Current Rating (ESQ/TSW):
5.7 A per pin
(2 pins powered)
Voltage Rating:
515 VAC/728 VDC
Insertion Depth:
(3.68 mm) .145" to
(6.35 mm) .250"
Max Cycles:
100 with 10 µ" (0.25 µm) Au

PROCESSING

Lead-Free Solderable:
No, Lead Wave only


ALSO AVAILABLE
Contact Samtec


Other Platings

Note:
Some lengths, styles and options are non-standard, non-returnable.

SERIES	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	OTHER OPTION
ESW = Solder Tail **ESQ** = Square Tail		01 thru 36	Specify LEAD STYLE from chart	**–F** = Gold flash on contact, Matte Tin on tail (ESW only) **–L** = 10 µ" (0.25 µm) Gold contact, Matte Tin on tail **–G** = 20 µ" (0.51 µm) Gold contact, Gold Flash on Balance **–T** = Matte Tin (Not available with LIF contact)	**–S** = Single Row **–D** = Double Row **–T** = Triple Row (ESQ only)	**–LL** = Locking Lead (Two leads per strip crimped. Not available with single row 1 or 2 positions) **"XX"** = Polarized

LEAD STYLE			
STANDARD INSERTION FORCE	LOW INSERTION FORCE	A	B
– 12	– 37	(2.29) .090	(11.05) .435
– 13	– 38	(7.36) .290	
– 23	– 48	(4.83) .190	(13.59) .535
– 33	– 58	(2.29) .090	(16.13) .635
– 14	– 39	(12.19) .480	(11.05) .435
– 24	– 49	(9.65) .380	(13.59) .535
– 34	– 59	(7.11) .280	(16.13) .635
– 44	– 69	(4.57) .180	(18.67) .735






APPLICATIONS

EMBEDDED-PC PC/104 MODULES

Self Nesting Sockets



(ESQ SERIES)

PC/104™ J1/P1 "Stackthrough" Connectors	
Standard Insertion Force	ESQ-132-14-G-D
Low Insertion Force	ESQ-132-39-G-D
PC/104™ J1 "Non-Stackthrough" Connectors	
Standard Insertion Force	ESQ-132-12-G-D
Low Insertion Force	ESQ-132-37-G-D
PC/104™ J2/P2 "Stackthrough" Connectors	
Standard Insertion Force	ESQ-120-14-G-D
Low Insertion Force	ESQ-120-39-G-D

PC/104 is a trademark of the PC/104 Consortium.

Unless otherwise approved in writing by Samtec, all parts and components are designed and built according to Samtec's specifications which are subject to change without notice.