

samtec

FLEX STACK

(2.54 mm) .100"



MTSW–117–09–G–D–383–RA



HMTSW–126–23–L–S–237


MODIFIED .025" SQ POST HEADERS

Board Mates:
SSW, SSQ, ESW,
ESQ, BCS, BSW
CES, SLW, HLE, SSM

Cable Mates:
IDSD, IDSS, SMSD, SMSS

Modified .025" strips permit custom post heights.

Samtec offers the greatest stacking flexibility in the industry. The "M" stands for Modified. You tell us the post height you need and we'll deliver it.



SPECIFICATIONS

For complete specifications see www.samtec.com?MTSW or www.samtec.com?HMTSW

Insulator Material:
MTSW: Black Glass Filled Polyester
HMTSW: Natural Liquid Crystal Polymer
Terminal Material:
Phosphor Bronze
Plating:
Au or Sn over 50 µ" (1.27 µm) Ni
Operating Temp Range:
-55 °C to +125 °C with Gold
-55 °C to +105 °C with Tin
RoHS Compliant:
Yes
Lead–Free Solderable:
MTSW: No, Wave Only
HMTSW: Yes

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality

FILE NO. E111594

FILE NO: 090871_0_000


Note:
These Series are non-standard, non-returnable.

TYPE STRIP	PIN PITCH	NO. PINS PER ROW	LEAD STYLE


MTSW = Modified Strip

HMTSW = Hi-Temp Modified Strip


–1 = (2.54 mm) .100" Pitch



–2 = (5.08 mm) .200" Pitch




Straight Pin Versions



Right Angle Versions


HMTSW –S & –D = 36 positions maximum



01 thru 50 = (2.54 mm) .100" Center Version

02 thru 25 = (5.08 mm) .200" Center Version

SPECIFY "LEAD STYLE" FROM CHART




LEAD STYLE	OAL
–06	(7.62) .300
–07	(10.92) .430
–08	(13.46) .530
–09	(18.54) .730
–10	(21.08) .830
–11	(23.62) .930
–12	(26.16) 1.030
–13	(31.24) 1.230
–21	(36.32) 1.430
–22	(16.00) .630
–23	(11.30) .445
–24	(12.19) .480
–27	(33.78) 1.330
–28	(28.70) 1.130

Due to technical progress, all designs, specifications and components are subject to change without notice.


All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.




MTSW–108–28–G–D–920



MTSW–126–08–T–S–229–RA



HMTSW–110–23–L–S–237



MTSW–115–09–L–S–229-RE

MTSW, HMTSW SERIES


PLATING OPTION

–F
= Gold flash on post, Matte Tin on tail

–L
= 10 µ" (0.25 µm) Gold on post, Matte Tin on tail

–G
= 10 µ" (0.25 µm) Gold on post, Gold flash on balance

–T
= Matte Tin



ROW OPTION

–S
= Single

–D
= Double

–T
= Triple


–Q
= Double Row .200" (5.08 mm) row space

POST HEIGHT

OTHER OPTION

–RA or **–RE** = Right-angle

–LL
= Locking Lead (N/A with –RE, N/A in single row 1 or 2 positions. Available on tails from (2.29 mm) .090" to (10.16 mm) .400" only)



Two leads per strip crimped in opposite directions on or near centerline. See TSW for availability.

–LA = –RA Option with –LL Option (Maximum "C" = (13.46 mm) .530)

POLARIZED OPTION

–"XXX"
= Polarized (Specify 'XXX' as position number)

ALSO AVAILABLE
(MOQ Required)

- Other platings


Contact Samtec.

–"XXXX" = "C" Dimension (Specify post height in INCHES – .005" (0.13 mm) increments)

FOR A = (2.29) .090				
LEAD STYLE	OAL	C MAXIMUM STRAIGHT	C MAXIMUM with/–RA	C MAXIMUM with/–RE
– 06	(7.62) .300	(2.79) .110	Not Available	Not Available
– 07	(10.92) .430	(6.10) .240	(3.30) .130	Not Available
– 08	(13.46) .530	(8.64) .340	(5.84) .230	(3.30) .130
– 09	(18.54) .730	(13.72) .540	(10.92) .430	(8.38) .330
– 10	(21.08) .830	(16.26) .640	(13.46) .530	(10.92) .430
– 11	(23.62) .930	(18.80) .740	(16.00) .630	(13.46) .530
– 12	(26.16) 1.030	(21.34) .840	(18.54) .730	(16.00) .630
* – 13	(31.24) 1.230	(26.42) 1.040	(23.62) .930	(21.08) .830
* – 21	(36.32) 1.430	(31.50) 1.240	(28.70) 1.130	(26.16) 1.030
– 22	(16.00) .630	(11.18) .440	(8.38) .330	(5.84) .230
* – 23	(11.30) .445	(6.48) .255	(3.68) .145	Not Available
* – 24	(12.19) .480	(7.37) .290	(4.57) .180	
* – 27	(33.78) 1.330	(28.96) 1.140	(26.16) 1.030	(23.62) .930
* – 28	(28.70) 1.130	(23.88) .940	(21.08) .830	(18.54) .730


*** Styles –21, –23, –24, –27 not available with –D Right-angle**
Styles –13, –21, –23, –24, –27, –28 not available with –T or –Q Right-angle

Straight Pin Versions $A = OAL - C - \frac{(2.54)}{.100}$



Right-Angle Versions (–RA Options) $A = OAL - C - \frac{(5.33)}{.210}$

Styles –21, –23, –24, –27 N/A with –D
Styles –13, –21, –23, –24, –27, –28 N/A with –T or –Q



Right-Angle Versions (–RE Options) Single Row Only

$A = OAL - C - \frac{(7.87)}{.310}$

