Data sheet

VG PG36-MS54 ZR 24-33

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Similar to illustration



In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.
The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.
Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

General ordering data

Version	VG MS ZR (standard brass cable gland, multiseal), Cable glands, PG 36, 9 mm, OD min. 24 - OD max. 33 mm, Brass, nickel-plated
Order No.	1009650000
Type	VG PG36-MS54 ZR 24-33
GTIN (EAN)	4032248714421
Qty.	10 items
Delivery status	Discontinued
Available until	2024-08-31T00:00:00+02:00
Alternative product	VG 36-MS68

Data sheet

VG PG36-MS54 ZR 24-33

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform

Dimensions and weights

Length	39 mm	Length (inches)	1.5354 inch
Net weight	132.7 g		

Temperatures

Operating temperature	-20 °C...80 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c
REACH SVHC	Lead 7439-92-1
SCIP	b5ff1f66-ddba-4739-9fc0-0521ddb52139

General information

Outer cable diameter, max.	33 mm	Outer cable diameter, min.	24 mm
Operating temperature range, max.	80 °C	Operating temperature range, min.	-20 °C
Halogen	No	AF size 1	47 mm
AF size 2	50 mm	Protection degree	IP54
Cable gland	PG	Basic material	Brass, nickel-plated
Seal insert	NBR	Notch multi-layer sealing diameter 1	24 mm
Notch multi-layer sealing diameter 2	27 mm	Notch multi-layer sealing diameter 3	30 mm
Notch multi-layer sealing diameter 4	33 mm	External thread	PG 36
Length of thread	9 mm	Torque for cap nut, max.	6.70 Nm
Torque for connecting adapter, max.	10.00 Nm	Torque for connecting adapter, min.	10.00 Nm
Torque for cap nut, min.	6.70 Nm		

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ETIM 8.0	EC000441	ETIM 9.0	EC000441
ETIM 10.0	EC000441	ECLASS 9.0	27-14-44-32
ECLASS 9.1	27-14-44-32	ECLASS 10.0	27-14-44-32
ECLASS 11.0	27-14-44-32	ECLASS 12.0	27-14-08-01
ECLASS 13.0	27-14-08-01	ECLASS 14.0	27-14-08-01
ECLASS 15.0	27-14-08-01		