
molex



**Part Number :** 1300061320
**Product Description :** Mini-Change A-Size Single-Ended Cordset, 5 Poles, Female (Straight) to Pigtail, 16 AWG, Rubber Cable, 7.62m (25.0') Length
**Series Number :** 130006
**Status :** Obsolete
**Product Category :** Industrial Cable Assemblies
**Engineering Part Number :** 105000C01F250

Obsolete

## Documents and Resources

### Drawings

1300061320_sd.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| China RoHS | Not Reviewed |
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Compliance Statements
- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

## Part Details

### General

| | |
|---|---|
| Status | Obsolete |
| Category | Industrial Cable Assemblies |
| Series | 130006 |
| Description | Mini-Change A-Size Single-Ended Cordset, 5 Poles, Female (Straight) to Pigtail, 16 AWG, Rubber Cable, 7.62m (25.0') Length |
| IP Rating | IP67 |
| Product Name | Mini-Change |
| Type | Single Ended |
| UPC | 78678844801 |

### Agency

| | |
|---|---|
| CSA | LR6837 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 8.0A |
| Voltage - Maximum | 600V |

### Physical

| | |
|---|---|
| Cable Diameter | 13.20mm (.520") |
| Cable Length | 7.62m (25.0') |
| Color - Cable Jacket | Yellow |
| Connector End A | Mini-Change |
| Connector End B | Pigtail |
| Coupling Style | Threaded |
| Gender | Female-Pigtail |
| Keyway | Single |
| LED Indicator | None |
| Material - Cable Jacket | Rubber |
| Material - Connector Body | PVC |

Obsolete

| | |
|---|---|
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Black Epoxy Coated Zinc |
| Material - Plating Mating | Gold |
| Orientation | Straight to Pigtail |
| Poles | 5 |
| Temperature Range - Operating | -20° to +90°C |
| Wire/Cable Type | SOOW |
| Wire Size (AWG) | 16 |



Obsolete