**Part Number :** 1200010710
**Product Description :** Micro-Change (M12) Single-Ended Cordset, 4 Poles, Female (Straight) to Pigtail, 20 AWG, 1.0m (3.28') Length
**Series Number :** 120001
**Status :** Obsolete
**Product Category :** Industrial Cable Assemblies
**Engineering Part Number :** 804000J11M010



## Documents and Resources

### Drawings

1200010710_sd.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Product not active |
| China RoHS | Product not active |
| EU ELV | Product not active |
| Low-Halogen Status | Product not active |
| REACH SVHC | Product not active |
| EU RoHS | Product not active |

Compliance Statements
- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Obsolete

CE - Declaration of Conformity

UKCA - Declaration of Conformity

## Part Details

### General

| | |
|---|---|
| Status | Obsolete |
| Category | Industrial Cable Assemblies |
| Series | 120001 |
| Description | Micro-Change (M12) Single-Ended Cordset, 4 Poles, Female (Straight) to Pigtail, 20 AWG, 1.0m (3.28') Length |
| IP Rating | IP67, IP68 |
| Product Name | Micro-Change (M12) |
| Type | Single Ended |
| UPC | 883906487744 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum | 250V AC/DC |

### Physical

| | |
|---|---|
| Cable Diameter | 6.10mm (.240") |
| Cable Length | 1.0m (3.28') |
| Color - Cable Jacket | Gray |
| Connector End A | Micro-Change (M12) |
| Connector End B | Pigtail |
| Coupling Style | Threaded |
| Gender | Female-Pigtail |
| Keyway | Single |
| LED Indicator | None |
| Material - Cable Jacket | PVC |
| Material - Connector Body | PVC |
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Teflon Nickel-plated Brass |
| Material - O-Ring | Viton |

Obsolete

| | |
|---|---|
| Material - Plating Mating | Gold |
| Net Weight | 74.506/g |
| Orientation | Straight to Pigtail |
| Poles | 4 |
| Temperature Range - Operating | 0° to +75°C |
| Wire/Cable Type | Unshielded PVC |
| Wire Size (AWG) | 20 |



Obsolete