Part Number : 1200675042
Product Description : M12 Signal, A-Coded, Double-Ended Cordset with LED for PNP Sensors,4 Poles, Female (90°) to Male (Straight), 0.34mm² (22 AWG), Black PUR/PVC Cable, 3.0m (9.84') Length
Series Number : 120067
Status : Active
Product Category : Industrial Cable Assemblies
Engineering Part Number : 8840P7P03M030



Documents and Resources

Drawings

1200675042_sd.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains TBBA; Triphenyl-phosphate; Lead per D(2025)7771-DC (04 Feb 2026)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Compliance Statements
- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

UKCA - Declaration of Conformity

CE - Declaration of Conformity

Part Details

General

Status	Active
Category	Industrial Cable Assemblies
Series	120067
Description	M12 Signal, A-Coded, Double-Ended Cordset with LED for PNP Sensors,4 Poles, Female (90°) to Male (Straight), 0.34mm² (22 AWG), Black PUR/PVC Cable, 3.0m (9.84') Length
IP Rating	IP67
Product Name	M12 Signal,Micro-Change (M12)
Type	Double Ended
UPC	883906268664

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	30V AC/DC

Physical

Cable Diameter	5.30mm (.209")
Cable Length	3.0m (9.84')
Color - Cable Jacket	Black
Connector End A	Micro-Change (M12)
Connector End B	Micro-Change (M12)
Coupling Style	Threaded

Gender	Female-Male
Keyway	A-Coded
LED Indicator	PNP Sensors
Material - Cable Jacket	PUR/PVC
Material - Connector Body	PUR
Material - Contact	Copper Alloy
Material - Coupling Nut	Nickel-plated Brass
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Net Weight	148.789/g
Orientation	90° to Straight
Poles	4
Temperature Range - Operating	-20° to +80°C
Wire/Cable Type	Flex
Wire Size (AWG)	22