Part Number : 1200678181
Product Description : M12 Signal, A-Coded, Single-Ended Cordset with Stainless-Steel Nut, 4 Poles, Female (Straight) to Pigtail with LED for NPN Sensors, 0.34mm² (22 AWG), Black PUR/PVC Cable, 5.0m (16.40') Length
Series Number : 120067
Status : Not Recommended For New Design
Product Category : Industrial Cable Assemblies
Engineering Part Number : 8040P0P03M0501



Documents and Resources

Drawings

1200678181_sd.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

Compliance Statements
- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

UKCA - Declaration of Conformity

CE - Declaration of Conformity

Part Details

General

Status	Not Recommended For New Design
Category	Industrial Cable Assemblies
Series	120067
Description	M12 Signal, A-Coded, Single-Ended Cordset with Stainless-Steel Nut, 4 Poles, Female (Straight) to Pigtail with LED for NPN Sensors, 0.34mm^2 (22 AWG), Black PUR/PVC Cable, 5.0m (16.40') Length
IP Rating	IP67
Product Name	M12 Signal,Micro-Change (M12)
Type	Single Ended
UPC	883906424084

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	30V AC/DC

Physical

Cable Diameter	5.30mm (.209")
Cable Length	5.0m (16.40')
Color - Cable Jacket	Black
Connector End A	Micro-Change (M12)
Connector End B	Pigtail
Coupling Style	Threaded
Gender	Female-Pigtail

Keyway	A-Coded
LED Indicator	NPN Sensors
Material - Cable Jacket	PUR/PVC
Material - Connector Body	PUR
Material - Contact	Copper Alloy
Material - Coupling Nut	Stainless Steel
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Net Weight	214.030/g
Orientation	Straight to Pigtail
Poles	4
Temperature Range - Operating	-30° to +90°C
Wire/Cable Type	Flex
Wire Size (AWG)	22