

**Part Number :** 1200870113
**Product Description :** Nano-Change (M8) Double-Ended Cordset, 5 Poles, B-Coded, Male (Straight) to Female (Straight), 24 AWG, Yellow PVC Cable, 2.0m (6.56') Length
**Series Number :** 120087
**Status :** Active
**Product Category :** Circular Industrial Cordsets
**Engineering Part Number :** 445030A10M020

## Documents & Resources

### Drawings

1200870113_sd.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | Not Relevant |
| EU ELV | Not Reviewed per 2000/53/EC |
| Low-Halogen Status | Not Relevant |
| REACH SVHC | Contains Lead per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

CE - Declaration of Conformity

UKCA - Declaration of Conformity

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Circular Industrial Cordsets |
| Series | 120087 |
| Description | Nano-Change (M8) Double-Ended Cordset, 5 Poles, B-Coded, Male (Straight) to Female (Straight), 24 AWG, Yellow PVC Cable, 2.0m (6.56') Length |
| IP Rating | IP67 |
| Product Name | Nano-Change (M8) |
| Protocol | N/A |
| Type | Double Ended |
| UPC | 78678832995 |

### Agency

| | |
|---|---|
| CSA | LR6837 |
| UL | E152210 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 3.0A |
| Voltage - Maximum | 30V AC / 36V DC |

### Physical

| | |
|---|---|
| Cable Diameter | 5.08mm (.200") |
| Cable Length | 2.0m (6.56') |
| Color - Cable Jacket | Yellow |
| Connector End A | Nano-Change (M8) |

| | |
|---|---|
| Connector End B | Nano-Change (M8) |
| Coupling Style | Threaded |
| Gender | Female-Male |
| Keyway | B-Coded |
| LED Indicator | None |
| Material - Cable Jacket | PVC |
| Material - Connector Body | TPE |
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Nickel-plated Brass |
| Material - O-Ring | Fluoro-elastomer |
| Material - Plating Mating | Gold |
| Net Weight | 254.000/g |
| Orientation | Straight to Straight |
| Poles | 5 |
| Temperature Range - Operating | -20° to +105°C |
| Wire/Cable Type | UL 2661 |
| Wire Size (AWG) | 24 |