**Part Number :** 1200980160
**Product Description :** Micro-Change (M12) Double-Ended Cordset, 5 Poles, B-Coded, Female (Straight) to Male (Straight), 24 AWG, 15.0m (49.21') Length, PROFIBUS PUR Cable Preferred Version in Europe
**Series Number :** 120098
**Status :** Active
**Product Category :** Circular Industrial Cordsets
**Engineering Number :** BB5S30PP4M150



## Documents & Resources

### Drawings

1200980160_sd.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Circular Industrial Cordsets |
| Series | 120098 |
| Description | Micro-Change (M12) Double-Ended Cordset, 5 Poles, B-Coded, Female (Straight) to Male (Straight), 24 AWG, 15.0m (49.21') Length, PROFIBUS PUR Cable Preferred Version in Europe |
| IP Rating | IP67 |
| Product Name | Micro-Change (M12) |
| Protocol | EtherNet |
| Type | Double Ended |
| UPC | 78172500036 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 4.0A |
| Voltage - Maximum | 60V AC/DC |

### Physical

| | |
|---|---|
| Cable Diameter | 8.00mm (.315") |
| Cable Length | 15.0m (49.21') |
| Color - Cable Jacket | Violet |
| Connector End A | Micro-Change (M12) |
| Connector End B | Micro-Change (M12) |
| Coupling Style | Threaded |
| Gender | Female-Male |

| | |
|---|---|
| Keyway | B-Coded |
| LED Indicator | None |
| Material - Cable Jacket | PUR |
| Material - Connector Body | PUR |
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Nickel-plated Brass |
| Material - Plating Mating | Gold |
| Net Weight | 1167.838/g |
| Orientation | Straight to Straight |
| Poles | 5 |
| Temperature Range - Operating | -20° to +80°C |
| Wire/Cable Type | Twisted Pair |
| Wire Size (AWG) | 24 |