**Part Number :** 1202540151
**Product Description :** Contrinex Photoelectric Sensor, M18 Housing, Reflex, PNP, Dark-ON, 2m 3-wire PVC Cable, 50mm Housing Length
**Series Number :** 120254
**Status :** Not Recommended For New Design
**Product Category :** Inductive and Photoelectric Sensors
**Engineering Part Number :** LRK-1180-304



## Documents & Resources

### Specifications

1202540150-000.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Not Reviewed per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

UKCA - Declaration of Conformity

CE - Declaration of Conformity

---

## Part Details

### General

| | |
|---|---|
| Status | Not Recommended For New Design |
| Category | Photoelectric Sensors |
| Series | 120254 |
| Description | Contrinex Photoelectric Sensor, M18 Housing, Reflex, PNP, Dark-ON, 2m 3-wire PVC Cable, 50mm Housing Length |
| IP Rating | IP67 |
| Operating Principle | Reflex |
| Product Name | Contrinex |
| Type | Photoelectric |
| UPC | 191130069170 |

### Electrical

| | |
|---|---|
| Output | Dark-ON |
| Polarity | PNP |
| Switching Frequency | ≤ 1000 Hz |

### Physical

| | |
|---|---|
| Connection | Cable (PVC 2m, 3-wire) |
| Length | 50mm |
| Material - Housing | Chrome Plated Brass |
| Material - Window | Glass |
| Output | Dark-ON |
| Sensor Housing Size | M18 |
| Temperature Range - Operating | -25° to +55°C |