**Part Number :** 1212080044
**Product Description :** mPm DIN Valve Connector, Form B-11mm, External Thread, 2 Pole Plus Ground with A1 Circuit, 12V, Green LED, Transparent, Nitrile Gasket
**Series Number :** 121208
**Status :** Active
**Product Category :** Circular Industrial Connectors
**Engineering Number :** S22200TA1A0R



## Documents & Resources

### Drawings

1212080044_sd.pdf

### Specifications

PK-121208-S22-001.pdf

PS-121201-001-001.pdf

STR-1251-001.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2022)9120-DC (17 Jan 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Circular Industrial Connectors |
| Series | 121208 |
| Description | mPm DIN Valve Connector, Form B-11mm, External Thread, 2 Pole Plus Ground with A1 Circuit, 12V, Green LED, Transparent, Nitrile Gasket |
| IP Rating | IP65, IP67 |
| Product Name | mPm |
| Type | Field Attachable Connector |
| UPC | 884982509627 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 16.0A |
| Voltage - Maximum | 12V |

### Physical

| | |
|---|---|
| Cable Diameter | N/A |
| Coupling Type | External Thread |
| Diagnostics / LEDs | Yes |
| Diagnostics Port | No |
| Form | B - 11mm |
| Gender | N/A |

| | |
|---|---|
| Keyway | None |
| Material - Connector Body | Polyamide |
| Material - Contact | Brass |
| Material - Coupling Nut | N/A |
| Material - Plating Mating | Silver |
| Net Weight | 19.489/g |
| Orientation | 90° Angle |
| Pitch - Mating Interface | 11.00mm |
| Poles | 2 |
| Temperature Range - Operating | -40°C to +90°C |
| Wire Size (AWG) | N/A |