Status: Active

Add to My Parts Email this page

PART NUMBER:
1300062464

Mini-Change A-Size Single-Ended Cordset, 3 Poles, Male (Straight) to Pigtail, 16 AWG, Yellow TPE Cable, 15.0m (49.21') Length

Series: 130006

Category: Industrial Cordsets

Overview: Brad Mini-Change Connectors

EngineeringOldPN:103006K13M150



Larger Image

Buy Now Request Design Support

Engineering Documents Environmental Part Details

Something Missing On This Page? Give Feedback

Engineering Documents

Specifications & Other Documents:

- Part Details (PDF)

Sales Drawings, 3D Models, and Brochures:

- Drawing (PDF)

Product Stewardship

Compliance:

EU ELV: Compliant with Exemption 3

EU RoHS: Compliant with Exemption 6(c)

China RoHS:

REACH SVHC: Contained Per -D(2020)9139-DC (19 Jan 2021)
more

Low-Halogen Status: Not Relevant

Documents:

EU RoHS Certificate of Compliance (PDF)

Multiple Part Product Compliance Statements
EU RoHS, REACH SVHC, & Low-Halogen

Multiple Part Industry Compliance Documents
*IPC 1752A Class C
*IPC 1752A Class D
*Molex Product Compliance Declaration
*IEC-62474
*chemSHERPA (xml)

California Sales: Click here for Proposition 65 information

View Molex Environmental Position Statements: Click here

Request Molex's CMRT from conflictminerals@molex.com

Part Details

Collapse All

General

Status	Active
Category	Industrial Cordsets
Series	130006
Connector End A	Mini-Change
Connector End B	Pigtail
IP Rating	IP67
Material - Contact	Copper Alloy
Overview	Brad Mini-Change Connectors
Product Name	Mini-Change
Region	America
Type	Single Ended
UPC	78172552171

Physical

Cable Diameter	10.41mm (.410")
Cable Length	15.0m (49.21')
Color - Cable Jacket	Yellow
Coupling Style	Threaded
Gender	Male-Pigtail
Keyway	Single
LED Indicator	No
Material - Cable Jacket	TPE
Material - Connector Body	TPE
Material - Coupling Nut	Black Epoxy Coated Zinc
Material - Plating Mating	Gold
Net Weight	1999.000/g
Orientation	Straight to Pigtail
Poles	3
Temperature Range - Operating	-20° to +105°C
Wire Size AWG	16
Wire/Cable Type	TC-ER

Electrical

(Please review the Product Specification for specific details.)

Current - Maximum per Contact	13.0A
Voltage - Maximum	600V

Agency Certification

(Please find UL Certificates by searching the UL Database using the Molex Series Number.)Click here to visit the UL Database

UL	E152210

Material Info

Engineering Number	103006K13M150

Reference - Drawing Numbers

Sales Drawing	SD-130006-068-001

Do you have any questions? Contact Us

Molex® is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners.

© Copyright 2021