**Part Number :** 1300830245
**Product Description :** Woodhead POW-R-MITE Industrial Duty Cable Reel, 14/3 SOW, 7.62m (25.0') Cord Length with 30W Maximum Incandescent Spot Light and Ball Stop
**Series Number :** 130083
**Status :** Active
**Product Category :** Electrical Reels
**Engineering Number :** 9253-1610S



## Documents & Resources

### Drawings

1300830245_sd.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| China RoHS | Not Reviewed |
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Compliance Statements
- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Electrical Reels |
| Series | 130083 |
| Description | Woodhead POW-R-MITE Industrial Duty Cable Reel, 14/3 SOW, 7.62m (25.0') Cord Length with 30W Maximum Incandescent Spot Light and Ball Stop |
| Comments | Applications: Vertical Lift, Drag, Recovery and Horizontal Stretch with 10% Sag. |
| Enclosure Rating | NEMA 4 |
| NEMA Configuration | N/A |
| Product Name | POW-R-MITE |
| Type | Cable Reel |
| UPC | 78678834993 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 13.0A |
| GFCI | No |
| Lamp Wattage - Maximum | 30W |
| On/Off Switch | Yes |
| Transformer Type | Reel Mounted |
| Voltage - Maximum | 120V |

### Physical

| | |
|---|---|
| Bulb Included | Yes |
| Cable Length | N/A |
| Cable Movement | Ratchet Lock |
| Cord Length | 7.62m (25.0') |
| Cord Type | 14/3 SOW |

| | |
|---|---|
| Depth | 0.34m (13.50") |
| Drum Lock | Ratchet |
| Duty | Industrial |
| Guide Arm | 5° increments over 270° Arc |
| Height | 0.37m (14.50") |
| Lamp Type | Incandescent |
| Material - Coating | Powder Coating |
| Material - Housing | Cast Aluminum |
| Mounting Style | Rigid |
| Number of Conductors | 3 |
| Number of Receptacles | 1 |
| Packaging Type | Carton |
| Primary Cord/Cable Entry | 1" NPT |
| Retraction Weight | 1.8kg (4.0 lb) |
| Width | 244.35mm (9.620") |
| Wire Size (AWG) | 14 |