**Part Number :** 1201088363
**Product Description :** Double-Ended RJ-45 Cordset, 4 Poles, Male (Straight) to Male (Straight), 22 AWG, Green Shielded TPE Cable, 15.0m (49.21') Length, 6.70mm (.264") Diameter
**Series Number :** 84702
**Status :** Active
**Product Category :** Industrial Cable Assemblies
**Engineering Part Number :** E66A06012M150



## Documents and Resources

### Drawings

1201088363_sd.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| China RoHS | Not Reviewed |
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Compliance Statements
- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Industrial Cable Assemblies |
| Series | 84702 |
| Description | Double-Ended RJ-45 Cordset, 4 Poles, Male (Straight) to Male (Straight), 22 AWG, Green Shielded TPE Cable, 15.0m (49.21') Length, 6.70mm (.264") Diameter |
| IP Rating | IP20 |
| Performance Category | 5e |
| Product Name | Industrial Ethernet |
| Type | Double Ended |
| UPC | 889056151085 |

### Agency

| | |
|---|---|
| UL | E200650 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 1.5A |
| Voltage - Maximum | 30V |

### Physical

| | |
|---|---|
| Cable Diameter | 6.70mm (.264") |
| Cable Length | 15.0m (49.21') |
| Color - Cable Jacket | Green |
| Connector End A | RJ-45 (standard) |
| Connector End B | RJ-45 (standard) |
| Coupling Style | Push and Latch |
| Gender | Male-Male |
| Keyway | None |
| LED Indicator | None |
| Material - Cable Jacket | TPE |
| Material - Connector Body | TPU |

| | |
|---|---|
| Material - Contact | Phosphor Bronze |
| Material - Coupling Nut | N/A |
| Material - Plating Mating | Gold |
| Net Weight | 1016.652/g |
| Orientation | Straight to Straight |
| Poles | 4 |
| Temperature Range - Operating | -40° to +80°C |
| Wire/Cable Type | Shielded TPE/AWM 21215 |
| Wire Size (AWG) | 22 |