
Part Number : 1300540012
Product Description : M12 Data, D-Coded, Micro-Change (M12) Single-Ended Receptacle, 4 Poles, D-Coded, Female (Straight) to Pigtail, Length 0.20m (7.87")
Series Number : 130054
Status : Active
Product Category : Industrial Cable Assemblies
Engineering Part Number : ERWAAJ4002M002



Documents and Resources

Drawings

1300540012_sd.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2020)9139-DC (19 Jan 2021)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

CE - Declaration of Conformity

UKCA - Declaration of Conformity

Part Details

General

Status	Active
Category	Industrial Cable Assemblies
Series	130054
Description	M12 Data, D-Coded, Micro-Change (M12) Single-Ended Receptacle, 4 Poles, D-Coded, Female (Straight) to Pigtail, Length 0.20m (7.87")
IP Rating	IP67
Performance Category	5e
Product Name	M12 Data,Micro-Change (M12),Industrial Ethernet
Protocol	EtherNet
Type	Single Ended
UPC	78678804662

Agency

UL	E200650

Electrical

Current - Maximum per Contact	1.5A
Voltage - Maximum	125V

Physical

Cable Diameter	N/A
Cable Length	0.20m (7.87")

Color - Cable Jacket	Teal
Connector End A	Micro-Change (M12)
Connector End B	Pigtail
Coupling Style	Threaded
Gender	Female-Pigtail
Keyway	D-Coded
LED Indicator	None
Material - Cable Jacket	PVC
Material - Connector Body	PVC
Material - Contact	Copper Alloy
Material - Coupling Nut	Nickel-plated Brass
Material - Plating Mating	Gold
Net Weight	32.380/g
Orientation	Straight to Pigtail
Poles	4
Temperature Range - Operating	-25° to +75°C
Wire/Cable Type	E152210
Wire Size (AWG)	24