
- Products
  - By Type
    - Connectors
    - Electromechanical Components
    - Electronic Modules
    - Fiber Optics
    - Filters
    - Identification & Labeling
    - Passive Components
    - Power Sources
    - RF & Microwave Products
    - Tooling Products
    - Touch Screen Displays
    - Tubing, Molded and Harnessing Products
    - Wire, Cable and Cable Assemblies
    - List all product types...
  - By Industry
    - Aerospace & Defense Products
    - Appliance
    - Automotive
    - Communications
    - Computer & Consumer Electronics
    - Industrial & Commercial
    - Instrumentation & Medical
  - By Brand
  - A to Z
  - Product News
- Documentation
  - Find Documents & Drawings
  - Find CAD Models
  - SPICE/Electrical Models
  - NAFTA Certificate of Origin
  - White Papers
- Resources
  - RoHS Compliance & Alternates
  - Cross Reference Products
  - Compare Multiple Products
  - Check Distributor Inventory
  - Find Authorized Distributors
- My Account
  - Sign In
  - Register
- Customer Support
  - Support
  - RoHS Support Center
  -

RP418012 Product Details



RP418012

Active

Mid-Range PC Board Relays

Converted to EU RoHS but not ELV Compliant (Statement of Compliance)

Product Highlights:

- RPII/1 Series
- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Contact Current Rating = 12 Amps.
- Monostable Coil Magnetic System
- Without Coil Suppression Diode

View all Features | Find Similar Products

Previous 1 2 [3] 4 5 ... 20 Next

Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Compare Products
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- Power PCB Relay RPII/1 (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- Product Line Information

Related Products:

- Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Termination Type = Through Hole

Electrical Characteristics:

- Contact Current Rating (Amps.) = 12
- Coil Resistance (?) = 270
- Coil Power, Nominal (mW) = 500
- Actuating System = DC
- Coil Power, Nominal (W) = 0.50
- Input Voltage (VDC) = 12
- Dielectric Strength - Coil Contacts (V rms) = 4000
- Tracking Resistance of Relay Base = PTI250

Body Related Features:

- Series = RPII/1
- Polarized = No
- Enclosure Color = Clear

Contact Related Features:

- Mounting Options = PC Board, Socket
- Enclosure = Flux-Tight
- FCC Part 68 Isolation = No
- Relay Type = PCB
- Contact Material = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm [in]) = 29.00 x 12.60 x 25.50 [1.141

Housing Related Features:

- Pick-Up (V) = 8.4
- Drop-Out (V) = 1.2

Configuration Related Features:

- Contact Arrangement = 1 Form C, SPDT, 1 C/O
- Coil Magnetic System = Monostable
- Coil Suppression Diode = Without
- Coil Selection Criteria = Nominal Voltage
- Coil Latching = Without
- LED Indicator = Without
- Number of Coils = 1

Industry Standards:

- RoHS/ELV Compliance = RoHS/Not ELV Compliant
- Lead Free Solder Processes = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives

Packaging Related Features:

- Packaging Method = Carton Bar

x .496 x 1.003]

- Contact Type = Single
- Pin Configuration = Industry Standard 3.5mm
- Wiring Diagram = 1 Form C
- Approved Standards = VDE Component Mark, UL Recognized for Canada and US
- Number of Poles = 1

Other:

- Electrical Spacing = 8.0mm Clearance 8.0mm Creepage
- Brand = Schrack

Provide Website Feedback | Contact Customer Support
Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support
2008 Tyco Electronics Corporation All Rights Reserved