ZTA 5/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image



Similar to illustration

Test adapters and test plugs are used for the electrical connection between terminal blocks and the test equipment. In this way, an electrical contact can be established in the wired state and measurements can be done easily.

General ordering data

Version	Accessories, Test adapter, 13.5 A
Order No.	1776220000
Type	ZTA 5/ZA
GTIN (EAN)	4032248190683
Qty.	25 pc(s).
Delivery status	Discontinued
Available until	2022-03-30

ZTA 5/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	54 mm	Depth (inches)	2.126 inch
Height	20 mm	Height (inches)	0.787 inch
Width	3.5 mm	Width (inches)	0.138 inch
Net weight	3.8 g		

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50
Continuous operating temp., max.	120		

Material data

Material	Wemid	Colour	black
UL 94 flammability rating	V-0		

System specifications

Version	For the terminals	Number of levels	1
Number of clamping points per level	1		

Additional technical data

Installation advice	Direct mounting	With snap-in pegs	Yes

Conductors for clamping (rated connection)

Clamping range, max.	1 mm²	Clamping range, min.	0.5 mm²
Number of connections	1	Stripping length	10 mm
Tightening torque, max.	0.3 Nm	Tightening torque, min.	0.3 Nm
Type of connection	Plug-in connection	Wire connection cross section, finely stranded, max.	1 mm²
Wire connection cross section, finely stranded, min.	0.5 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	1 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.5 mm²	Wire connection cross-section, solid core, max.	1 mm²
Wire connection cross-section, solid core, min.	0.5 mm²		

Dimensions

Height with TS 35	54 mm

General

Installation advice	Direct mounting	Number of poles	1

Rating data

Rated cross-section	1 mm²	Rated voltage	200 V
Rated DC voltage	200 V	Rated current	13.5 A
Volume resistance according to IEC 60947-7-x	2.37 mΩ	Power loss in accordance with IEC 60947-7-x	0.43 W

ZTA 5/ZA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC002555	ETIM 7.0	EC002555
ETIM 8.0	EC002555	ETIM 9.0	EC002555
ECLASS 9.0	27-14-11-48	ECLASS 9.1	27-14-11-48
ECLASS 10.0	27-14-11-48	ECLASS 11.0	27-14-11-48
ECLASS 12.0	27-14-11-48	ECLASS 13.0	27-25-03-04

Approvals

ROHS	Conform

Downloads

Engineering Data	CAD data – 31288_ZTA_5-ZA_DXF.dxf CAD data – STEP
Engineering Data	Zuken E3.S
User Documentation	Beipackzettel_ZTA_5.pdf StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	