
## Sew Clamp 32/35 mm DIN-Rail Terminals Disconnect

| | | SAKC 4 | | SAKC 10 | |
|---|---|---|---|---|---|
| | |  | |  | |
| **Dimensions** | | | | | |
| Width/Length/Height mm (in.) | With TS 35 x 7.5 ⎓ | 6.5 / 49.5 / 42.5/59.5 (.26/1.95/2.34) | | 12 / 65 / 66 (.47/2.56/2.6) | |
| | With TS 32 ⊏⎓ | 6.5 / 40 / 51.5/67 (.26/1.57/2.04) | | 12 / 65 / 52.5/70.5 (.47/2.56/2.76) | |
| Insulation stripping length | mm (in.) | 12 (.47") | | 12 (.47") | |
| **Technical data** | | | | | |
| Rated voltage/rated current/wire size | UL | 300V / 25A / #22...12 AWG | | 600V / 25A / #22...8 AWG | |
| | CSA | 300V / 25A / #22...10 AWG | | 600V / 25A / #20...10 AWG | |
| | VDE | 380VAC / 25A / 4mm² | | 500VAC / 27A / 10mm² | |
| Torque | Nm (lb. in.) | 0.6 / 0.5 StB (7.0) | | 3.0 (26.0) | |
| *Clamping screw* | M | 3 | | 4 | |
| **Ordering data** | **Version** | ⊏⎓ | ⎓ | ⊏⎓ | ⎓ |
| | KrG | **34072** | **35752** | **32402** | |
| | KrS | | | **32403** | |
| With 2 StB | KrG | **34062** | **35762** | **32412** | **140462** |
| With 1 StB | KrG | | | | **140452** |
| With 2 StB | KrS | | | **32413** | |
| **End plate (thickness mm)** | | **Type** | **Cat. No.** | **Type** | **Cat. No.** |
|  | KrG | AP (1.5) | **11792** | AP (3.0) | **14672** |
| | KrS | | | AP (3.0) | **14673** |
| | PA | | | | |
| **Partition (thickness mm)** | | | | | |
| | KrG | | | TW (3.0) | **24292** |
|  | KrS | | | TW (3.0) | **24293** |
| | PA | TW (1.5) | **13016** | TW (1.5) | **24296** |
| | HP | TW (1.0) | **29710**** | | |
| **Jumpers** | | | | | |
|   | | QB 2* | **48270** | QL 2 | **13550** |
| | | QB 3* | **48280** | QL 3 | **13560** |
| | | QB 4* | **48290** | QL 4 | **13570** |
| | | | | QL 10 | **33850** |
| | | QB 25 bare* | **13400** | | |
| | | | | VH 14 | **29970** |
| | | | | BS M 4x20 | **36280** |
| | | | | SS M 4 | **13640** |
| **Jumpering link** | | | | | |
|  VL BS VH | | | | | |
| **Dummy plug** | | | | | |
|  | Made of plastic, to keep the place of a pulled plug | BST 4 green | **133905** | | |
| | | BST 4 red | **133906** | | |
| | | BST 4 blue | **133908** | | |
| **Test plug/Socket** | | | | | |
|  | Plug/test socket usable without QL | | | StB 13.5 | **13520** |
| | For #18 AWG wire | PS 2.3 | **18040** | | |
| | For #14 AWG wire | | | PS 4 | **29960** |
| **Disconnector plug (spare)** | | | | | |
| | | TST | **138060** | TST | **46270** |
| ***Extraction tool*** | | | | | |
| For TST | | – | **62306** | | |
| **Marking tags** | **Print** | | | | |
| Note: Part numbers are shown for a single card of pre-printed tags numbered 1-50. For additional information, see section 5. | Consecutive horizontal | FW 6.5 | **468160001** | FW6 | **468660001** |
| | Vertically printed | FS 6.5 | **468260001** | FS6 | **468760001** |

***See Section 5 for mounting rails, end brackets, test taps, additional marking material and accessories***

* When using QB, the rated cross-section is reduced to max. 2.5mm² ** For TS 32 only *** With AP 380V